Modular Lighting 729 120X30 Low Glare 4000K DALI2

REF. **72951333-684**

BASIC INFORMATION

MATERIAL	APPLICATION	ETIM CLASS
Aluminium	Office	EC002892

TECHNICAL INFORMATION

FREQUENCY	POWER SUPPLY (V~)	COLOR TYPE
50 - 60 Hz	220/240 V~	NW

IP RATING	CONTROL
IP20	On/Off

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT
50

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053305171

UNITARY PACKAGING HEIGHT
35

UNITARY PACKAGING WIDTH
39

UNITARY PACKAGING LENGTH
122.2

UNITARY PACKAGING MEASUREMENT UNIT
MMT

UNITARY PACKAGING VOLUME
166803

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
2

PRODUCT NET WEIGHT
1.75

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053305171

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
0

PACKAGING WIDTH
0

PACKAGING LENGTH
0

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
0

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0

PACKAGING NET WEIGHT
1.75

PACKAGING WEIGHT UNIT
KGM