COOL downlight mini Surface-mounted 3000 K Flood White

REF. **91031102-300**

BASIC INFORMATION

BODY MATERIAL
Die-cast aluminium

PACKAGING CONTENTS
1 Unit

APPLICATION
Domestic,Office,Retail,Hotel,Contract

PACKAGING DIMENSIONS (MM)
84x305x270 mm

TECHNICAL INFORMATION

FREQUENCY
50 - 60 Hz

IP RATING
IP20

OPERATING TEMPERATURE RANGE (ºC)
0 - 35 ºC

POWER SUPPLY (V~)
100/240 V~

RAL
9016

COLOR TEMPERATURE (K)
3000 K

CONTROL
1-10 V

CRI
80

DIRECTIONAL
No

DRIVER INCLUDED
Yes

ENERGY EFFICIENCY
A+

L70 (ºC)
60000h at 25ºC

L90 (ºC)
25000h at 25ºC

COLOR TYPE
NW

LIGHTING EFFICIENCY (LM/W)
83 lm/W

LUMENS (LM)
1150 lm

NUMBER OF LUMINAIRES
1

MACADAM STEPS
<3 Step MacAdam

OPTICS
Flood 25º

POWER FACTOR (Φ)
0,9

POWER (W)
15 W

INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES
Flush-mounted

INSTALLATION TYPE
Surface-mounted

REGULATIONS

EAC MARKED
Yes

ECORRAE MARKED
Yes

WARRANTY
5 years

LOGISTICS INFORMATION

UNITARY EAN CODE
8436547031689

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
1.774

PRODUCT NET WEIGHT
1.6

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8436547031689

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
84

PACKAGING WIDTH
270

PACKAGING LENGTH
305

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
6.12

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
1.76

PACKAGING NET WEIGHT
1.6

PACKAGING WEIGHT UNIT
KGM