

Adjustable depth trap on 2 modules S for installation in a false floor graphite color Simon CIMA

REF. SF210/14



BASIC INFORMATION

FINISH

Graphite

MATERIAL

Various

COMPATIBILITY

With Simon Series S and Simon 25 / Simon K45 (using adapter) mechanisms.

ETIM CLASS

EC000024

TECHNICAL INFORMATION

NUMBER OF CLAMP-HOLDER HOLES

4

HEAT RESISTANCE (°C)

+125 °C (in accordance with standard IEC 60695-10-2)

IK CLASSIFICATION

08

IP RATING

IP4X

KIT AVAILABILITY

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

MAXIMUM LOAD (KG)

1400kg

RAL

7021

RECESS DIMENSION (MM)

170 x 155 mm

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS

Only with tool

REMOVAL OF COVER

Only with tool

REMOVAL OF THE FRAME

Only with tool

NUMBER OF COVER OPENING POSITIONS

2

EXTINGUISHING (°C)

+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-2-11)

LOGISTICS INFORMATION

UNITARY EAN CODE

8426436052567

UNITARY PACKAGING HEIGHT

100

UNITARY PACKAGING WIDTH

190

UNITARY PACKAGING LENGTH

175

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

3.325

UNITARY PACKAGING VOLUME UNIT

DMQ

UNITARY PACKAGING GROSS WEIGHT

1.15

PRODUCT NET WEIGHT

1.15

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8426436052567

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

100

PACKAGING WIDTH

190

PACKAGING LENGTH

175

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

3.325

PACKAGING VOLUME UNIT

DMQ

PACKAGING GROSS WEIGHT

1.15

PACKAGING NET WEIGHT

1.15

PACKAGING WEIGHT UNIT

KGM