

Waterproof luminaire 780 IP65 5000 K 1200 DALI

REF. 78031333-885



BASIC INFORMATION

DESCRIPTION

The 780 waterproof luminaire, made with an extruded PC body, is perfect for lighting car parks, industries, underpasses, storage areas, humid spaces, etc. Its LED technology allows it to switch on instantly and avoid flickering. The luminaire is IP65 and IK08 rated and comes in 3 different sizes and versions with 1-10 V / DALI dimming.

APPLICATION

Car park lighting, Industrial lighting

PACKAGING CONTENTS

1 unit

ETIM CLASS

EC002892

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

CRI

80

LUMENS/W

4400 lm/40W

IK CLASSIFICATION

08

ELECTRICAL CLASS

Type 2

OPTICS

General

IP RATING

IP65

L70 (°C)

50,000 h at 25°C

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

OPERATING TEMPERATURE RANGE (°C)

-20 - 35 °C

LIGHT BEAM APERTURE ANGLE (°)

120°

POWER (W)

40 W

POWER SUPPLY (V~)

220/240 V~

COLOR TYPE

CW

SERVICE LIFE

50.000 h

COLOR TEMPERATURE (K)

5000 K

LIGHTING EFFICIENCY (LM/W)

110 lm/W

CONTROL

DALI

LUMENS (LM)

4400 lm

CHROMATICS CRI ICONS

CRI
80

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

Surface-mounted / Wall /
Suspended

REGULATIONS

WARRANTY

5 years 50.000 h

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053217191

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

1.188

PRODUCT NET WEIGHT

0.916

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053217191

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

1250

PACKAGING WIDTH

64

PACKAGING LENGTH

63

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

5040000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

1.188

PACKAGING NET WEIGHT

0.916

PACKAGING WEIGHT UNIT

KGM