Downlight 800.24 White 35W 3000K DALI2

REF. **80024330-283**

BASIC INFORMATION

APPLICATION	PACKAGING CONTENTS	ETIM CLASS
General technical lighting	1 Units	EC001744

TECHNICAL INFORMATION

FREQUENCY
50 - 60 Hz

IP RATING
IP54

OPERATING TEMPERATURE RANGE (ºC)
-15ºC a 35ºC

POWER SUPPLY (V~)
220/240 V~

COLOR TEMPERATURE (K)
3000K

CONTROL
DALI2

COS Φ
0.95

CRI
80

ELECTRICAL CLASS
tipo 2

L70 (ºC)
50.000 h a 25ºC

LIGHT BEAM APERTURE ANGLE (°)
60º

COLOR TYPE
WW

LIGHTING EFFICIENCY (LM/W)
100 lm/W

LUMENS (LM)
3400 lm

LUMENS/W
3400 lm/35W

OPTICS
Extensive

PHOTOBIOLOGICAL CLASSIFICATION
Categoría exento

POWER (W)
35W

SERVICE LIFE
50.000 h

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT
130

INSTALLATION TYPE
Recessed

TYPE OF TERMINAL CONNECTION - FUNCTION 1
Quick connector

REGULATIONS

WARRANTY
5 years 50.000 h

REGULATIONS
Dir. 2014/35/UE LVD |Dir. 2014/30/UE EMC|Dir. 2009/125/EC ErP (Reg. UE 2019/2020) |Dir. 2009/125/EC ErP (Reg. UE 2019/2015)|Dir. 2011/65/UE RoHS + post. mod|EN 60598-2-2:2012 |EN IEC 55015:2019 + A11:2020|EN 62493:2015 |EN 61547:2009|EN 62717:2017 + A2:2019 |EN IEC 61000-3-2:2019 + A1:2021|EN IEC 63000:2018 |EN 61000-3-3:2013 + A1:2019 + A2:2021

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053304556

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
1.09

PRODUCT NET WEIGHT
0.974

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053304556

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
145

PACKAGING WIDTH
250

PACKAGING LENGTH
215

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
7793750

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
1.09

PACKAGING NET WEIGHT
0.974

PACKAGING WEIGHT UNIT
KGM