

Flat voice and data plate without dust cover for 1 RJ45 Panduit® for 1 element graphite Simon 500 Cima

REF. 50019185-038



BASIC INFORMATION

DESCRIPTION

Flat base plate of voice and data in graphite colour, with 1 element for 1 RJ45 connector Panduit ®. It measures 50x50x11 mm and is made of halogen-free thermoplastic, in compliance with the regulation. It is a material that guarantees the no-propagation of the flame in the event of a fire, and low toxicity if there is the presence of gas. The plate does not with dust shutter, but clips for optimum fastening in vertical and horizontal enclosures without using adapter. It is ideal to place the piece in environments whose temperature ranges between 5 and 60 °. To clean it, simply use a soft, dry cloth and give light passes. This mechanism is included in the Simon 500 Cima series, a collection designed to provide maximum workplace solutions to work places. It is the ideal solution for any environment.

FINISH

Graphite

PACKAGING CONTENTS

Flat voice and data plate without dust cover

ETIM CLASS

EC000018

COMPATIBILITY

Simon 500 Cima enclosures

REMARKS

The plate is snap-fitted for mounting in vertical and horizontal enclosures without the need for an adaptor.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST SHUTTER

No

NUMBER OF MODULES

1

AVAILABLE IN

Plate for 1 and 2 RJ45

FORMAT

RJ45

PLATE TYPE

Flat

COMPATIBLE WITH CONNECTORS

Panduit® Mini-Com Series.

IP RATING

IP20

RAL

7021

RJ45 CONNECTORS

Not included in voice and data plate

KIT AVAILABILITY

No

RJ45 ADAPTOR MODULE

Included in voice and data plate

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT RJ45 PLATES

RJ45 Panduit® connectors

SNAP-FIT TYPE

RJ45 Panduit® connectors

DUST PROTECTION

No

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

VERSION

Single

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Specific Simon 500 Cima

INSTALLATION DIRECTION

Vertical, corresponding with the direction of the mechanisms

INSTALLATION TYPE

Fixing by direct snap-fit, no tools needed.

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053097151

PACKAGING VOLUME

0.604

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

10

PACKAGING VOLUME UNIT

DMQ

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

54

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING GROSS WEIGHT

0.027

PACKAGING WIDTH

52

PACKAGING NET WEIGHT

0.27

PRODUCT NET WEIGHT

0.027

PACKAGING LENGTH

215

PACKAGING WEIGHT UNIT

KGM

