2-way switch with key 2.5A 250V~ 3 positions (key removable in rest position) and welding terminal connection ivory Simon 27 Play

REF. **27523-62**



BASIC INFORMATION

DESCRIPTION

The 2-way switch of the Simon Play 27 series is the perfect if what you are looking for is skew a current of a circuit or directly suspend it. It is suitable for elements of up to 2.5 A current and 250 volts and works by key of 3 positions. It is necessary to highlight the key is removable in rest position. The rocker operation is carried out by welding and the device is very easy to install, by means of recessed or directly on the surface-mounted, offering two options to the user. It comes in an original and stylish finished in ivory colour. It measures 45 x 45 millimetres and is made up of two modules, in addition, it is a product that stands out for its manufacturing materials that give it a high resistance and extra security. These are metal elements, halogen-free, and the trim is made of thermoplastic, the features of these materials make the final product is able to work in optimum low temperatures very low and high.

FINISH

Ivory

COMPATIBILITY

Simon 27 Play, Simon 27 Neos, Simon 27 Scudo, Simon 27, Simon 27 Centralisations and Simon 44 Aqua frames

PACKAGING CONTENTS

Mechanism with cover

ETIM CLASS

EC001590

REMARKS

Mechanism with 2 positions and removable key in rest position.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CABLE SECTION ADMITTED (MM)

0,5 mm

NUMBER OF POSSIBLE ELEMENTS

1 element

INDICATOR FUNCTION

No

CURRENT (A)

2,5 A

IP RATING

IP20

KEY-REMOVAL POSITION

Standby

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TYPE OF MECHANISM

Key

NOMINAL VOLTAGE (V~)

250 V~

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

VERSION

Single

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

7

CLAW

Included

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, American and Centralisations

INSTALLATION TYPE

Suitable for surface and flush mounting

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Welding

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD|Dir. 2011/65/UE RoHS + post. mod.|EN IEC 61058-1:2018 |EN 61058-1-1:2016|EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053082140

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
0.095

PRODUCT NET WEIGHT
0.095

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053082140

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
81

PACKAGING WIDTH
82

PACKAGING LENGTH
90

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
0.598

PACKAGING VOLUME UNIT
DMQ

PACKAGING GROSS WEIGHT
0.095

PACKAGING NET WEIGHT
0.095

PACKAGING WEIGHT UNIT
KGM