Complete kit with cover, brush, 4 schuko socket outlets and plate for 4 RJ45 connectors black S400 Indesk

REF. **44604040-138**



BASIC INFORMATION

DESCRIPTION

Simon offers us a complete kit integrated into the table with a cover and brush, capacity for 4 schukos for standard power and a plate for 4 RJ45 connectors finished in black from the Simon 400 Indesk series. A piece with dimensions of 295 x 185 x 85 millimeters created to seamlessly integrate into any space, thanks to its great design and manual lift system. It has 4 bases for standard power circuit of 250 volts and 16 amperes. As with all Simon products, quality is ensured; this kit features a painted steel housing, an anodized aluminum profile, covers and supports made of self-extinguishing thermoplastic and halogen-free that guarantee no flame spread in the event of a fire and low toxicity in the event of smoke emission.

FINISH

Black

MATERIAL

Metal

COMPATIBILITY

Can be combined with the range of Electric Cabling from Simon.

PACKAGING CONTENTS

Pre-wired profile, enclosure, fastening claws and installation manual.

ETIM CLASS

EC002759

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

PROTECTION AGAINST DIRECT ACCESS OF CONTACTS
No

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS
Yes, thanks to the included protective cover and cable outlet with brush

DIELECTRIC STRENGTH
No holes or contours, with 2000V at 50 Hz for 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)
+60°C

FORMAT
Schuko

HEAT RESISTANCE (°C)
+70°C (according to standard IEC 60670)

INSULATION RESISTANCE (V-MΩ)
>5 M? at 500 V

CURRENT (A)
16 A

IP RATING
IP30

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 at +60° C

NOMINAL VOLTAGE (V~)
250 V~

TYPE OF POWER SUPPLY CONNECTOR
Wieland® GST 18i male 3-pole overhead connector with 22 cm patch cord

RAL
9005

RECESS DIMENSION (MM)
318 x 175 mm (± 2mm)

NUMBER OF RJ45 WINDOWS
4

SNAP-FIT RJ45 PLATES
Keystone® I, II and Systimax®

SNAP-FIT TYPE
Keystone® I, II and Systimax®

NUMBER OF SOCKETS
4 sockets for standard current circuit

VERSION
6 elements

INSTALLATION AND MAINTENANCE

CABLING ACCESS
With brush

CLAW RANGE OF OPERATION (MM)
Between 20 and 40 mm

NUMBER OF COVER OPENING POSITIONS
1

EXTINGUISHING (ºC)
+70 ºC (according to standard IEC 60670)

TYPE OF FASTENING
By tightening existing clamps in the fastening bracket.

REMOVAL OF THE FRAME
Only with tool

INSTALLATION TYPE
Suitable for recessed mount in furniture.

OPENING ORIENTATION
At 45

SECURING POSSIBILITIES
Using supplied claws or screws in the available holes

MOUNTING WITHOUT ACCESSORIES
Supplied with all necessary materials for installation.

REGULATIONS

REGULATIONS
Directiva 2014/35/UE LVD;Directiva 2011/65/UE RoHS;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;IEC 60884-1 Ed 3.2;

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053208328

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
2.1

PRODUCT NET WEIGHT
2.1

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053208328

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
275

PACKAGING WIDTH
195

PACKAGING LENGTH
90

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
4826250

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0

PACKAGING NET WEIGHT
2.1

PACKAGING WEIGHT UNIT
KGM