

Accessory for joining trays IP66 in concrete floor Simon K45

REF. ACSE



BASIC INFORMATION

DESCRIPTION

A its watertight floor boxes with the ACSE accessory for junction IP66 trays for concrete floor within the collection Simon K45 made of metal and finishes in Aluminium, offers the perfect design for a room stylish, with the maximum security, workplace solutions and resistance. If you need more than one connection point, the ACSE accessory it facilitates the connection of trays to any of the 4 sides. Thanks to its design, makes it possible to the grouping of trays, within the perimeter of the same, to have more link points. Its composition in metal finished in Aluminium, it allows you to achieve a temperature range of installation of -25°C and 60 ° C, being able to they cannot be exceeded in construction. With this accessory with IP66 protection rating, keeping all the product isolated from water and dust. Security, innovation and functionality with a minimalist design in all of the range Simon K45. With the range update, its equivalent for the new version is the KFA1002 reference.

FINISH

Aluminium

COMPATIBILITY

Mounting boxes art. KGE170 / 23
Simon K45

PACKAGING CONTENTS

IP66 tray joint accessory in
concrete floor

MATERIAL

Metal

ETIM CLASS

EC002420

REMARKS

If you need more than one connection point, the ACSE accessory allows you to connect trays to any of the 4 sides.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

MAX TEMP DURING CONSTRUCTION WORK (°C)

+90° C

INSULATION RESISTANCE (V-MΩ)

>5 MOhm at 500 V

DIELECTRIC STRENGTH

Without perforation or
contournement with 2000 V at
50H during 1 minute

HEAT RESISTANCE (°C)

+70°C (according to standard IEC
60670)

TEMPERATURE RANGE DURING INSTALLATION (°C)

-25 a 60° C

INSTALLATION AND MAINTENANCE

EXTINGUISHING (°C)

+650 °C (according to standard IEC 60670)

TYPE OF FASTENING

The joint accessory is fastened on to the housings defined for this purpose and distributed around the sides of the tray.

INSTALLATION DIRECTION

The box union is done according to the vertical position of the accessory.

INSTALLATION TYPE

Thanks to its design, trays for the concrete floor can be grouped around the entire tray perimeter, with more than one connection point.

REGULATIONS

REGULATIONS

UNE-EN 60.670-23

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.021

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING VOLUME

514500

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8426436036789

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

51450

UNITS CONTAINED PACKAGING

10

PACKAGING GROSS WEIGHT

0.215

UNITARY PACKAGING VOLUME
UNIT

MMQ

PACKAGING HEIGHT

70

PACKAGING NET WEIGHT

0.21

UNITARY PACKAGING GROSS
WEIGHT

0.021

PACKAGING WIDTH

70

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

105