

Charger USB type A+C port 18W QuickCharge aluminium Simon K45

REF. K126F/8



BASIC INFORMATION

FINISH

Aluminium

MATERIAL

Thermoplastic

COMPATIBILITY

K45 Solutions. 500 Cima solutions via adapter 50012088-033.

ETIM CLASS

EC002949

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

IP RATING

IP20

RECESS DIMENSION (MM)

40

NUMBER OF CONNECTORS

2

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

USB CHARACTERISTICS

QC 18W

CONNECTOR TYPE

USB A + USB C

QUICK CHARGE USB

Yes

NUMBER OF CONTACTS

2

PLATE TYPE

Flat

VOLTAGE (V~)

230 V~

FORMAT

USB A + USB C

POWER SUPPLY (V~)

230 V~

NUMBER OF WIRES

2

RAL

9006

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

10

EXTINGUISHING (°C)

+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-10-2)

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Screw

REMOVAL OF CONNECTOR

Only with tool

INSTALLATION DIRECTION

Horizontal, Vertical

TYPE OF TERMINAL CONNECTION - FUNCTION 2

Screw

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053313442

UNITARY PACKAGING HEIGHT

55

UNITARY PACKAGING WIDTH

65

UNITARY PACKAGING LENGTH

65

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

232375

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.079

PRODUCT NET WEIGHT

0.079

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053313442

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

55

PACKAGING WIDTH

65

PACKAGING LENGTH

65

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

232375

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.82

PACKAGING NET WEIGHT

0.079

PACKAGING WEIGHT UNIT

KGM