SUB-D25 connector (parallel port) female with trim plate black Simon K45

REF. **K104A/14**



BASIC INFORMATION

DESCRIPTION

This connector is within the series of Simon K45 and it is a female SUB-D25 connector (parallel port). The product is included the trim plate. Its measures are 90 x 45 millimetres and its installation is very simple and can be perform by flush mounted or directly on the surface-mounted, which gives versatility to the product. Its type of clamping is by welding and works by insertion. The maximum length of cabling recommended is 30 meters. The connector is available in an original and innovative black colour, that endow of modernity to any room in the home, office or premises where it is placed. Its components are equipped with self-extinguishing halogen-free thermoplastic insulation, so that in case of fire does not contribuirían to expand the fire and also are able to reduces the toxicity of smoke. Also gives it great resistance to the product that is able to work optimally low temperatures ranging from -25 to 50 degrees centigrade.

FINISH

Black

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-038)

PACKAGING CONTENTS

Female SUB-D25 connector (parallel port)

ETIM CLASS

EC000018

REMARKS

Maximum wire length recommended; 30 meters For additional information, please read the product instruction sheet

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

CABLE SECTION ADMITTED (MM)
From 0,2 to 0,5 mm

CONNECTOR TYPE
Sub-D25

NUMBER OF CONTACTS
25

NUMBER OF POSSIBLE ELEMENTS
2 elements

IP RATING
IP20

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

OPERATING TEMPERATURE RANGE (°C)
5 - 40 °C

RAL
7021

STORAGE TEMPERATURE RANGE (°C)
-25 - 50 °C

VERSION
Single

NUMBER OF WIRES
25

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX
Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-038)

INSTALLATION TYPE
Suitable for surface and flush mounting

REGULATIONS

REGULATIONS
Dir. 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
70

UNITARY PACKAGING WIDTH
93

UNITARY PACKAGING LENGTH
140

UNITARY PACKAGING MEASUREMENT UNIT
MMT

UNITARY PACKAGING VOLUME
0.3

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.038

PRODUCT NET WEIGHT
0.038

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436045439

UNITS CONTAINED PACKAGING
5

PACKAGING HEIGHT
70

PACKAGING WIDTH
93

PACKAGING LENGTH
140

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
911.4

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.2

PACKAGING NET WEIGHT
0.19

PACKAGING WEIGHT UNIT
KGM