

## IP66 Mechanism holder and manual frame with 2 schuko and 2 RJ45 Keystone lodge

REF. KFH211/72



## BASIC INFORMATION

### DESCRIPTION

Simon completely renews its range of watertight floor boxes for indoor and outdoor environments. This is a manual closing mechanism frame with 2 schuko sockets and a housing for 2 RJ45 Keystone connectors. In combination with its bucket, it will allow for installation in technical floors or pavement. The product design, combined with its stainless steel construction, achieves a robust, solid, and secure installation as it withstands a water jet of 1 kg/cm<sup>2</sup> from any direction, reaching an IP66 protection rating when the lid is closed. It also supports a maximum load of 2000 kg and has an IK08 impact resistance. It maintains an optimal cable bending radius for high-category voice and data connections. Our accessory for connection with a closed lid is available, allowing us to keep our connections active with an IP54 (see reference KFA1001), the possibility to level our box in case of uneven flooring (see reference KFA1003), or the ability to link more than one box (see reference KFA1002).

### FINISH

Steel

### COMPATIBILITY

K45 Solutions

### MATERIAL

Polycarbonate

### ETIM CLASS

EC000024

### REMARKS

To complete the installation of the product, it must be combined with a tray for the IP66 waterproof floor box.

## TECHNICAL INFORMATION

### FORMAT

Schuko

### IP RATING

IP66

### MAXIMUM LOAD (KG)

2000 Kg - Closed box | 250 Kg - Open box

### IK CLASSIFICATION

08

### KIT AVAILABILITY

Yes

### VOLTAGE (V~)

250 V~

### CURRENT (A)

16 A

### MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

## INSTALLATION AND MAINTENANCE

### REMOVAL OF COMPONENTS

Only with tool

### EXTINGUISHING (°C)

+650 °C (according to standard IEC 60670)

### REMOVAL OF THE SOCKET

Only with tool

### NUMBER OF COVER OPENING POSITIONS

1

### REMOVAL OF THE FRAME

Only with tool

## REGULATIONS

### REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2011/65/UE RoHS + post. mod. | EN 60670-23:2008 | EN IEC 63000:2018 | IEC 60884-1 Ed 3.2 | UNE 20315-1-1:2017 | UNE 20315-1-2:2017

## LOGISTICS INFORMATION

### UNITARY EAN CODE

8421053334850

### UNITARY PACKAGING HEIGHT

0

### UNITARY PACKAGING WIDTH

0

### UNITARY PACKAGING LENGTH

0

### UNITARY PACKAGING MEASUREMENT UNIT

MMT

### UNITARY PACKAGING VOLUME

0

### UNITARY PACKAGING VOLUME UNIT

MMQ

### UNITARY PACKAGING GROSS WEIGHT

0.773

### PRODUCT NET WEIGHT

0.68

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING EAN

8421053334850

### UNITS CONTAINED PACKAGING

1

### PACKAGING HEIGHT

114

### PACKAGING WIDTH

125

### PACKAGING LENGTH

180

### PACKAGING MEASUREMENT UNIT

MMT

### PACKAGING VOLUME

2565000

### PACKAGING VOLUME UNIT

MMQ

### PACKAGING GROSS WEIGHT

0.773

### PACKAGING NET WEIGHT

0.68

### PACKAGING WEIGHT UNIT

KGM