

Hinged cover for adjustable floor box or service cover in concrete or raised floor for 6 elements grey Simon 500 Cima

REF. RSF003/1



BASIC INFORMATION

DESCRIPTION

This hinged lid is within the series of Simon 500 Cima, and is perfect for an adjustable floor box or service cover for a power supply of energy to a total of 6 elements. In addition, it is designed to be installed by recessing in concrete or raised floor. It is necessary to highlight the adjustable floor boxes of Simon already include the hinged lid, but the signature offers the possibility of acquiring this cover separately to use it in case of replacement. The cover is made up of 6 modules and measures 199 x 160 millimetres and 15 millimetres of depth. It is a beautiful finished in grey colour that you integrate perfectly anywhere, providing a touch of modernity and style. The product has a great resistance and an extra hardness, since it is manufactured with metallic components with self-extinguishing and halogen-free thermoplastic insulation.. These materials also mean that the fire box does not spread in case of fire and is able to reduces the toxicity of smoke.

FINISH

Grey

PACKAGING CONTENTS

Hinged cover

MATERIAL

Plastic

ETIM CLASS

EC001903

REMARKS

The adjustable floor boxes include the hinged cover. Only necessary to order it as a replacement part in the event of breakage or loss.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

PROTECTION AGAINST DIRECT ACCESS OF CONTACTS

No

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS

Yes, thanks to the inclusion of protective foam

AVAILABLE IN

2, 4, 6, 8 and 12 elements

DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)

+90 °C

HEAT RESISTANCE (°C)

+125°C (according rule IEC 60695-10-2)

INSULATION RESISTANCE (V-MΩ)

>5 MOhms at 500V

KIT AVAILABILITY

Yes

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

NUMBER OF MODULES

6 modules

RAL

7011

VERSION

6 elements

INSTALLATION AND MAINTENANCE

REMOVAL OF COVER

Only with tool

EXTINGUISHING (°C)

+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-2-11)

TYPE OF FASTENING

Via coupling pin supplied on the cover

INSTALLATION DIRECTION

Horizontal, Vertical

INSTALLATION TYPE

In raised or concrete floor with adjustable floor boxes or service covers

REGULATIONS

REGULATIONS

UNE-EN 60.670-23

LOGISTICS INFORMATION

UNITARY EAN CODE

8426436056213

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8426436056213

PACKAGING VOLUME

1.75

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

DMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

20

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

350

PACKAGING NET WEIGHT

0.702

UNITARY PACKAGING GROSS
WEIGHT

0.702

PACKAGING LENGTH

250

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

0.702