Aluminum trunking of 2m 160x55mm with 2 compartments for K45 functions

REF. **TK11122/8**



BASIC INFORMATION

DESCRIPTION

Aluminum channel with a length of 2m and a section of 165x55mm, featuring 2 front compartments capable of mounting all functions of the K45 range without the need for accessories, resulting in significant time savings during assembly. Regardless of the designed structure, it ensures the isolation of electrical wiring from voice, data, and multimedia, as well as maintaining its correct bending radius throughout the distribution. It adapts to various architectures through its installation accessories, with the possibility of branching to Mini-channel and Cable guide via the pre-stamped line. Made of high-quality anodized aluminum, it is equipped with an IP4X and IK07 protection rating. We are talking about a fireproof material, self-extinguishing, and non-flame propagating. The indicated price is per meter and is supplied in batches of 4 units (8 meters in total)

FINISH

Aluminium

COMPATIBILITY

Functions K45

MATERIAL

Aluminium

ETIM CLASS

EC001938

TECHNICAL INFORMATION

IK CLASSIFICATION
09

IP RATING
IP4X

KIT AVAILABILITY
No

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS
Only with tool

REMOVAL OF COVER
No tools needed

REMOVAL OF THE FRAME
Only with tool

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053264225

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
0

PRODUCT NET WEIGHT
2.5

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436027916

UNITS CONTAINED PACKAGING
8

PACKAGING HEIGHT
190

PACKAGING WIDTH
157

PACKAGING LENGTH
2020

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
60256600

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
20

PACKAGING NET WEIGHT
20

PACKAGING WEIGHT UNIT
KGM