ARCH Downlight X-Less Accessory Round 1 Network 1-10 V

REF. **91591019-999**



BASIC INFORMATION

APPLICATION

Domestic,Office,Retail,Hotel,Contract

PACKAGING DIMENSIONS (MM)

90x115x169 mm

PACKAGING CONTENTS

1 Unit

ETIM CLASS

EC002556

TECHNICAL INFORMATION

FREQUENCY
50 - 60 Hz

IP RATING
IP20 / IP43

OPERATING TEMPERATURE RANGE (ºC)
0 - 35 ºC

POWER SUPPLY (V~)
220/240 V~

CONTROL
1-10 V,Push Dim

COS Φ
0.94

DIRECTIONAL
No

DRIVER INCLUDED
No

ELECTRICAL CLASS
II

ENERGY EFFICIENCY
A+

LIGHTING EFFICIENCY (LM/W)
111 lm/W

PHOTOBIOLOGICAL CLASSIFICATION
Class II

POWER FACTOR (Φ)
> 0,55

INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES
Flush-mounted, Surface-mounted

INSTALLATION TYPE
Trimless

REGULATIONS

EAC MARKED
Yes

ECORRAE MARKED
Yes

WARRANTY
5 years

LOGISTICS INFORMATION

UNITARY EAN CODE
8436547036677

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
0.44

PRODUCT NET WEIGHT
0.32

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8436547036677

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
100

PACKAGING WIDTH
160

PACKAGING LENGTH
175

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
0.028

PACKAGING VOLUME UNIT
HLT

PACKAGING GROSS WEIGHT
0.44

PACKAGING NET WEIGHT
0.32

PACKAGING WEIGHT UNIT
KGM