Aluminium mini column with 1 side for 6 elements graphite Simon 500 Cima

REF. **52550113-033**



BASIC INFORMATION

DESCRIPTION

It is a mini column made in anodised aluminium of 1 side and designed for 6 elements with a graphite finish, measures 439 x 110 x 72 mm and is suitable for installing on any floor type, whether raised or concrete flooring. The product is in compliance with current regulations. By the shape of the baseboard, it is possible to integrate this mini column to the floor trunking 85x18 mm For the maintenance of this piece, it is recommended to clean it with a soft dry cloth and of soft texture. It is advisable, also, avoid abrasive cleaners containing chlorine, as they could damage it. The mini-column belongs to the Simon 500 Cima series, a collection that stands out for offering a system of innovative connectivity solutions and 50% faster installation, thanks to the revolutionary method of click-terminals connection, which consists of inserting and tightening, without stripping cables.

FINISH

Aluminium

MATERIAL

Aluminium

COMPATIBILITY

Simon 500 Cima and Simon 27 Play/Simon K45 mechanisms (using an adaptor)

PACKAGING CONTENTS

Mini column, baseboard, lower and upper trim, non-slip adhesive foam, fixing studs, ground connection cable, screws and installation manual

ETIM CLASS

EC001941

REMARKS

The shape of the baseboard allows integration of the mini column with the 85 x 18 mm floor trunking

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

PROTECTION AGAINST DIRECT ACCESS OF CONTACTS
No

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS
Yes, thanks to the inclusion of protective foam

AVAILABLE IN
1 and 2 sides

MAX TEMP DURING CONSTRUCTION WORK (°C)
+120 °C

EARTHING RESISTANCE
< 0.05 Ohms

ELECTRICAL PROPERTIES
With electrical continuity

ELECTROMAGNETIC IMMUNITY FOR VDM WIRING
Constant clearance between electric wiring and Voice, Data and Multimedia cables, eliminating electromagnetic interference and possible transmission errors.

IP RATING
IP4X

KIT AVAILABILITY
No

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)
-25 to +120 °C

NUMBER OF MODULES
6

VERSION
1 side

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS
Only with tool

TYPE OF FASTENING
Using the screws supplied

INSTALLATION DIRECTION
Vertical

INSTALLATION TYPE
Suitable for installing in any floor type, raised or concrete

SCREWS REQUIRED FOR FLOOR FIXING
4

REMOVAL OF TRIM FRAMES
Only with tool

REGULATIONS

REGULATIONS
Directive 2014/35/UE LVD + EN 50085-2-4:2009

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053094372

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
1.485

PRODUCT NET WEIGHT
1.485

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053094372

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
85

PACKAGING WIDTH
128

PACKAGING LENGTH
867

PACKAGING MEASUREMENT UNIT
MMT


PACKAGING VOLUME
15847200


PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0

PACKAGING NET WEIGHT
1.485

PACKAGING WEIGHT UNIT
KGM


76
72
110


451