Adjustable recessed box with 2 elements for installation on false floor graphite Simon K45

REF. **KF210/14**



BASIC INFORMATION

FINISH	MATERIAL	ETIM CLASS
Graphite	Various	EC000024

TECHNICAL INFORMATION

NUMBER OF CLAMP-HOLDER HOLES
2

HEAT RESISTANCE (°C)
+125 °C (in accordance with standard IEC 60695-10-2)

IK CLASSIFICATION
08

IP RATING
IP4X

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

MAXIMUM LOAD (KG)
800kg

RAL
7021

RECESS DIMENSION (MM)
170 x 115 mm

INSTALLATION AND MAINTENANCE

NUMBER OF COVER OPENING POSITIONS
2

REMOVAL OF COVER
Only with tool

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053125311

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
0.76

PRODUCT NET WEIGHT
0.76

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053125311

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
95

PACKAGING WIDTH
155

PACKAGING LENGTH
195

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
2871375

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.76

PACKAGING NET WEIGHT
0.76

PACKAGING WEIGHT UNIT
KGM