# Pin for unlocking security shutter of double socket outlet red Simon 500 Cima

REF. **50000803-039**



## BASIC INFORMATION

### DESCRIPTION

Pin for unlocking security shutter of the double socket-outlets. The product has a vibrant and modern finished in red colour and belongs to the Simon 500 Cima series. This is, specifically, the version of two elements and its dimensions are exact 30 x gone up 17.3 millimetres and a depth of 23,3 millimetres. It is very important to know that this reference is only compatible with the double socket-outlets for pin. It is made from a material thermoplastically, halogen-free, to prevent the propagation of the fire management and which minimizes the toxicity in the event of that exist a release of gas. This pin is suitable for combining with double socket-outlets to be installed both in surface-mounted and flush mounted. Its maintenance only requires the cleaning the product with a soft and completely dry cloth, free of cleaning products that are abrasive with the manufacturing materials.

### FINISH

Red

### MATERIAL

Plastic

### COMPATIBILITY

Double socket outlets for pin Simon 500 Cima

### PACKAGING CONTENTS

Pin for unlocking the security shutter

### ETIM CLASS

EC002461

### REMARKS

This article is only compatible with the double socket outlets for pin.

## TECHNICAL INFORMATION

### AVAILABLE MARKET

CE

### MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C in surface-mount wall installation and +90 °C in flush-mount wall installation

### IP RATING

IP20

### KIT AVAILABILITY

Yes

### MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

### RAL

3002

### VERSION

2 elements

## INSTALLATION AND MAINTENANCE

### REMOVAL OF COVER
Only with tool

### TYPE OF FASTENING
By direct snap-fit in the housing of the double socket outlet provided for that purpose (no tools needed for fastening))

### INSTALLATION DIRECTION
Vertical, corresponding with the direction of the mechanisms

### INSTALLATION TYPE
Suitable for combining in flush or surface-mount double socket outlets

## REGULATIONS

### REGULATIONS
UNE 20.315 / EN 60.998-2-3

## LOGISTICS INFORMATION

### UNITARY PACKAGING HEIGHT
0

### UNITARY PACKAGING WIDTH
0

### UNITARY PACKAGING LENGTH
0

### UNITARY PACKAGING VOLUME
0

### UNITARY PACKAGING GROSS WEIGHT
0.001

### PRODUCT NET WEIGHT
0.001

### UNITARY PACKAGING WEIGHT UNIT
KGM

### PACKAGING EAN
8421053099186

### UNITS CONTAINED PACKAGING
20

### PACKAGING HEIGHT
23

### PACKAGING WIDTH
57

### PACKAGING LENGTH
84

### PACKAGING MEASUREMENT UNIT
MMT

### PACKAGING VOLUME
110.124

### PACKAGING VOLUME UNIT
CMQ

### PACKAGING GROSS WEIGHT
0

### PACKAGING NET WEIGHT
0.02

### PACKAGING WEIGHT UNIT
KGM

23,3
30
17,3