

Downlight 725.25 WW Comfort High Flux 1-10 V

REF. 72525130-883



BASIC INFORMATION

APPLICATION

Accent lighting, General lighting

PACKAGING CONTENTS

1 unit

ETIM CLASS

EC001744

TECHNICAL INFORMATION

IP RATING

IP44

DRIVER INCLUDED

Yes

LUMENS (LM)

3300 lm

OPERATING TEMPERATURE RANGE (°C)

-10 - 35 °C

L70 (°C)

30,000 h

LUMENS/W

3300 lm/37W

COLOR TEMPERATURE (K)

3000 K

LIGHT BEAM APERTURE ANGLE (°)

120°

OPTICS

General

CONTROL

1-10 V

COLOR TYPE

WW

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

CRI

80

LIGHTING EFFICIENCY (LM/W)

89,2 lm/W

POWER (W)

37 W

CHROMATICS CRI ICONS

CRI
80

INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Surface-mounted

INSTALLATION TYPE

Flush-mounted

REGULATIONS

WARRANTY

3 years

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053089675

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

1.084

PRODUCT NET WEIGHT

0.861

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053089675

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

117

PACKAGING WIDTH

257

PACKAGING LENGTH

257

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

7727733

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

1.084

PACKAGING NET WEIGHT

0.861

PACKAGING WEIGHT UNIT

KGM