Kit 2 LOOP Wall-mounted luminaires + 1 driver On/Off White

REF. **91229954B300**

BASIC INFORMATION

BODY MATERIAL	APPLICATION	PACKAGING CONTENTS
Die-cast aluminium	Domestic,Office,Retail,Hotel,Contract	2 Unites

simon

TECHNICAL INFORMATION

FREQUENCY
50 - 60 Hz

IP RATING
IP20

OPERATING TEMPERATURE RANGE (ºC)
0 - 35 ºC

POWER SUPPLY (V~)
110/240 V~

RAL
9016

COLOR TEMPERATURE (K)
3000 K

CONTROL
On/Off

CRI
80

DIRECTIONAL
Yes

DRIVER INCLUDED
Yes

ELECTRICAL CLASS
II

ENERGY EFFICIENCY
A+

L70 (ºC)
20000h at 25ºC

LIGHT BEAM APERTURE ANGLE (°)
112º

COLOR TYPE
NW

LIGHTING EFFICIENCY (LM/W)
hasta 26 lm/W

LUMENS (LM)
154 lm

NUMBER OF LUMINAIRES
2

MACADAM STEPS
<3 Step MacAdam

OPTICS
General 112º

POWER FACTOR (Φ)
> 0,9

POWER (W)
6 W

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE
Trimless

REGULATIONS

EAC MARKED
Yes

ECORRAE MARKED
Yes

WARRANTY
3 years

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
0

PRODUCT NET WEIGHT
0

UNITARY PACKAGING WEIGHT UNIT
KGM

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
0

PACKAGING WIDTH
0

PACKAGING LENGTH
0

PACKAGING VOLUME
0

PACKAGING GROSS WEIGHT
0

PACKAGING NET WEIGHT
0