Customisable set with 4 schuko socket outlets and 2 empty elements black S400 Top

REF. **42604000-138**



BASIC INFORMATION

DESCRIPTION

Obtain the maximum quality of their connections in the work area thanks to the kit for desk top of the collection Simon 400 Top. Designed to extend the functionalities in a single mechanism and facilitate connectivity of their dispositvos, this kit Simon with finishes in black, it consists of 4 socket-outlets type Schuko socket and 2 empty elements. Also, and to optimise the space such as the functions of the mechanism, it is possible to personalize it, according to your needs. Manual elevation, its power supply is enlaza to connectors Wieland gst 18i 3-pole male in-line and with patch cord of 22 cm It is compatible with a voltage of 250 Volt power and current of 16 amps. It also has a insulation resistance > 5 M? at 500 V. Designed for flush installation, is fixed to the space by clamps pages and has a size of 295 x 120 mm and a depth of 80 mm, to ensure the complete integration of the set in the space.

FINISH

Black

MATERIAL

Metal

COMPATIBILITY

Functions of the Simon 400 range, combinable with the Simon Electric Cabling range.

PACKAGING CONTENTS

Pre-wired profile, table-top supports, rear trim cover and installation manual.

ETIM CLASS

EC002759

REMARKS

To complete the product installation combine it with the Simon 400 functions (refs. 400XXXXX-03X).

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

DIELECTRIC STRENGTH
No holes or contours, with 2000V at 50 Hz for 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)
+60°C

NUMBER OF POSSIBLE ELEMENTS
2

FORMAT
Schuko

HEAT RESISTANCE (°C)
+70°C (according to standard IEC 60670)

INSULATION RESISTANCE (V-MΩ)
>5 M? at 500 V

CURRENT (A)
16 A

IP RATING
IP30

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 at +60° C

NOMINAL VOLTAGE (V~)
250 V~

TYPE OF POWER SUPPLY CONNECTOR
Wieland® GST 18i male 3-pole overhead connector with 22 cm patch cord

RAL
9005

NUMBER OF REAR ENTRANCES
2

NUMBER OF SOCKETS
4 sockets for standard current circuit

VERSION
6 elements

INSTALLATION AND MAINTENANCE

CLAW RANGE OF OPERATION (MM)
Between 16 and 40 mm

REMOVAL OF COMPONENTS

EXTINGUISHING (°C)
+70 °C (according to standard IEC 60670)

TYPE OF FASTENING
By tightening existing clamps in the fastening bracket.

INSTALLATION TYPE
Suitable for fixing to furniture.

REMOVAL OF THE PLATE
Only with tool

SECURING POSSIBILITIES
Using clips included in the fastening brackets

MOUNTING WITHOUT ACCESSORIES
Supplied with all necessary materials for installation.

REGULATIONS

REGULATIONS

Directiva 2014/35/UE LVD;Directiva 2011/65/UE RoHS;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;IEC 60884-1 Ed 3.2;

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053196120

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
1.05

PRODUCT NET WEIGHT
1.05

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053196120

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
330

PACKAGING WIDTH
125

PACKAGING LENGTH
95

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
3918750

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0

PACKAGING NET WEIGHT
1.05

PACKAGING WEIGHT UNIT
KGM