

Voice and data flat plate with dust cover for 1 element for 2 RJ45 compatible other manufacturers white Simon K45

REF. KB76/9



BASIC INFORMATION

DESCRIPTION

The plate of voice and data flat plate with dust cover with 1 element for 2 RJ45 connectors is fully compatible with other manufacturers and is part of the collection K45 Simón. It measures 45x45 mm, a thickness of 8.5 mm with and a few simple yet versatile finishes white in colour, it is also made of halogen-free thermoplastic, which guarantees no flame propagation in case of fire and the low toxicity if any diara smoke. And it is that the commitment Simon is to offer the maximum quality in products in terms of trends. Therefore, its collection Simon K45 offers the best in terms of workplace solutions to meet to the most demanding performances.

FINISH

White

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-03X)

PACKAGING CONTENTS

Flat voice and data plate with dust cover

ETIM CLASS

EC000018

REMARKS

When combining the voice and data plate in vertical housings (mini columns, columns, Teleblock, channels, mechanism holders, etc.) you must use the 90° positioner (ref. K66) to guide the plate into a vertical position.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

AVAILABLE IN

Plate for 1 and 2 RJ45 connectors

COMPATIBLE WITH CONNECTORS

Simon®, ADC Krone® Series KM8 Keystone, AMP netconnect® Series SL110 and SL Tool less, BeldenCDT® Series Giga Flex Keystone, Ersys®, General Cable®, Molex®, Nexans® Series essential Keystone,Ortronics® Series Clarity TechChoice Keystone, Panduit® Series Netkey, R&M® Series Advance Cat6A (R509508, R509509), Rit®, Siemon® Series MAX Keystone, Systimax® and manufacturers of RJ45 with snap-fit based on the Keystone I and II format.

RJ45 CONNECTORS

Not included in voice and data plate

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

DUST PROTECTION

Yes

DUST SHUTTER

Yes

FORMAT

RJ45

IP RATING

IP20

KIT AVAILABILITY

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

NUMBER OF MODULES

Half

PLATE TYPE

Flat

RAL

9003

RJ45 ADAPTOR MODULE

Included in voice and data plate

SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

SNAP-FIT TYPE

Keystone I, II, ATT®/Avaya®

VERSION

Single

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-030)

INSTALLATION DIRECTION

Vertical according to the direction of the mechanisms

INSTALLATION TYPE

Suitable for surface and flush mounting

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053264010

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0.045

UNITARY PACKAGING VOLUME UNIT

DMQ

UNITARY PACKAGING GROSS WEIGHT

0.015

PRODUCT NET WEIGHT

0.015

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8426436065833

UNITS CONTAINED PACKAGING

20

PACKAGING HEIGHT

70

PACKAGING WIDTH

93

PACKAGING LENGTH

140

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

0.911

PACKAGING VOLUME UNIT

DMQ

PACKAGING GROSS WEIGHT

0.3

PACKAGING NET WEIGHT

0.3

PACKAGING WEIGHT UNIT

KGM