ARCH Downlight X-Less connection Accessory Network

REF. **91592019-000**



BASIC INFORMATION

APPLICATION	PACKAGING CONTENTS	ETIM CLASS
Domestic,Office,Retail,Hotel,Contract	1 Unit	EC002556

TECHNICAL INFORMATION

FREQUENCY
50 - 60 Hz

IP RATING
IP20 / IP43

OPERATING TEMPERATURE RANGE (ºC)
0 - 35 ºC

POWER SUPPLY (V~)
110/240 V~

DIRECTIONAL
No

DRIVER INCLUDED
No

ELECTRICAL CLASS
II

ENERGY EFFICIENCY
A+

LIGHTING EFFICIENCY (LM/W)
111 lm/W

PHOTOBIOLOGICAL CLASSIFICATION
Class II

POWER FACTOR (Φ)
> 0,9

INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES
Flush-mounted, Surface-mounted

INSTALLATION TYPE
Trimless

REGULATIONS

EAC MARKED
Yes

ECORRAE MARKED
Yes

WARRANTY
5 years

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053219942

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
0.15

PRODUCT NET WEIGHT
0.03

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053219942

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
50

PACKAGING WIDTH
50

PACKAGING LENGTH
50

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
125000

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.15

PACKAGING NET WEIGHT
0.03

PACKAGING WEIGHT UNIT
KGM