

3-phase rail Surface-mounted 2 m White

REF. 99920230-039



BASIC INFORMATION

APPLICATION

Domestic,Office,Retail,Contract

PACKAGING CONTENTS

1 Unit

TECHNICAL INFORMATION

OPERATING TEMPERATURE RANGE (°C)

0 - 35 °C

CONTROL

On/Off

DRIVER INCLUDED

No

RAL

9016

DIRECTIONAL

No

ENERGY EFFICIENCY

A+

INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Flush-mounted

INSTALLATION TYPE

Surface-mounted

REGULATIONS

EAC MARKED

No

ECORRAE MARKED

No

WARRANTY

3 years

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8436547037186

PACKAGING VOLUME

2450000

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

35

PACKAGING GROSS WEIGHT

1.77

UNITARY PACKAGING GROSS WEIGHT

0

PACKAGING WIDTH

35

PACKAGING NET WEIGHT

1.77

PRODUCT NET WEIGHT

1.77

PACKAGING LENGTH

2000

PACKAGING WEIGHT UNIT

KGM