Downlight 800.23 Black 24W 3000K DALI2

REF. **80023338-683**

BASIC INFORMATION

APPLICATION

General technical lighting

PACKAGING CONTENTS

1 Units

TECHNICAL INFORMATION

FREQUENCY
50 - 60 Hz

CRI
80

LUMENS/W
2400 lm/24W

IP RATING
IP54

ELECTRICAL CLASS
tipo 2

OPTICS
Extensive

OPERATING TEMPERATURE RANGE (ºC)
-15ºC a 35ºC

L70 (ºC)
50.000 h a 25ºC

PHOTOBIOLOGICAL CLASSIFICATION
Categoría exento

POWER SUPPLY (V~)
220/240 V~

LIGHT BEAM APERTURE ANGLE (°)
60º

POWER (W)
24W

COLOR TEMPERATURE (K)
3000K

COLOR TYPE
WW

SERVICE LIFE
50.000 h

CONTROL
DALI2

LIGHTING EFFICIENCY (LM/W)
105 lm/W

COS Φ
0.95

LUMENS (LM)
2400 lm

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT
115

INSTALLATION TYPE
Recessed

TYPE OF TERMINAL CONNECTION - FUNCTION 1
Quick connector

REGULATIONS

WARRANTY

5 years 50.000 h

REGULATIONS

Dir. 2014/35/UE LVD |Dir. 2014/30/UE EMC|Dir. 2009/125/EC ErP (Reg. UE 2019/2020) |Dir. 2009/125/EC ErP (Reg. UE 2019/2015)|Dir. 2011/65/UE RoHS + post. mod|EN 60598-2-2:2012 |EN IEC 55015:2019 + A11:2020|EN 62493:2015 |EN 61547:2009|EN 62717:2017 + A2:2019 |EN IEC 61000-3-2:2019 + A1:2021|EN IEC 63000:2018 |EN 61000-3-3:2013 + A1:2019 + A2:2021

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0.974

PRODUCT NET WEIGHT

0.974

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053308035

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

145

PACKAGING WIDTH

250

PACKAGING LENGTH

215

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

7793750

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

1.192

PACKAGING NET WEIGHT

0.974

PACKAGING WEIGHT UNIT

KGM