

Modular luminaire 726 60x60 Low Glare WW DALI

REF. 72660333-683



BASIC INFORMATION

DIFFUSER MATERIAL

PMMA

PACKAGING CONTENTS

1 unit

APPLICATION

General lighting

ETIM CLASS

EC002892

TECHNICAL INFORMATION

FREQUENCY (HZ)

50 - 60 Hz

DRIVER INCLUDED

Yes

LUMENS (LM)

2900 lm

IP RATING

IP20

ELECTRICAL CLASS

Tipo 2

LUMENS/W

2900 lm/39W

OPERATING TEMPERATURE RANGE (°C)

-15 - 40 °C

INTEGRATED POWER SUPPLY

No

OPTICS

Microprismatic

POWER SUPPLY (V~)

100/240 V~

L70 (°C)

30,000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION

Exempted category

COLOR TEMPERATURE (K)

3000 K

LIGHT BEAM APERTURE ANGLE (°)

90°

POWER (W)

39 W

CONTROL

DALI

COLOR TYPE

WW

SERVICE LIFE

30.000 h

CRI

80

LIGHTING EFFICIENCY (LM/W)

74 lm/W

CHROMATICS CRI ICONS

CRI
80

INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Plaster ceiling, surface mount, flush mount, concealed profile and suspended

MINIMUM INSTALLATION HEIGHT

250

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Screw

INSTALLATION TYPE

False ceiling, visible hardware

REGULATIONS

WARRANTY

3 years 30,000 h

LOGISTICS INFORMATION

UNITARY PACKAGING GROSS WEIGHT

3

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING LENGTH

0

PRODUCT NET WEIGHT

2.1

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING WEIGHT UNIT

KGM

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053193969

PACKAGING GROSS WEIGHT

3

PACKAGING HEIGHT

55

PACKAGING LENGTH

650

PACKAGING NET WEIGHT

2.1

UNITS CONTAINED PACKAGING

1

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

25918750

PACKAGING VOLUME UNIT

MMQ

PACKAGING WEIGHT UNIT

KGM

PACKAGING WIDTH

725