Industrial bell 819 60-100W CCT 120°

REF. **81941038-787**



BASIC INFORMATION

DESCRIPTION

Luminaire designed for industrial applications, suitable for high installations. High versatility thanks to its power and color temperature selector, allowing the luminaire to be adapted to each project with a single reference. Type of installation: Suspended. Optics: 120º. Color temperature: 3000 / 4000 / 5000K. Power: 60 - 80 - 100W. Lumens: 18000lm. Efficiency: 180lm/w. Protection grade IP: IP65. Power supply: 100-240 V. 50/60 Hz. Dimensions: 278 mm x 148 mm.

APPLICATION

General lighting for high ceilings,Industrial lighting

TECHNICAL INFORMATION

FREQUENCY
50 - 60 Hz

IK CLASSIFICATION
09

IP RATING
IP65

OPERATING TEMPERATURE RANGE (°C)
-30...+45

POWER SUPPLY (V~)
100/240 V~

CONTROL
1-10 V

LIGHTING EFFICIENCY (LM/W)
180 lm/W

LUMENS (LM)
18000 lm

POWER (W)
60 - 80 - 100 W

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE
Suspension

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053440216

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
2.1

PRODUCT NET WEIGHT
1.53

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053440216

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
145

PACKAGING WIDTH
325

PACKAGING LENGTH
325

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
15315625

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
2.1

PACKAGING NET WEIGHT
1.53

PACKAGING WEIGHT UNIT
KGM