

Downlight 735.20 WW Medium 1-10V white

REF. 73520130-683



BASIC INFORMATION

DESCRIPTION

Downlight 735.20 series, with Ecorrae category B and optics type Medium. Its colour temperature is 3000K and its light intensity of 2300 lm / 24 W and a frequency of 50 Hz. It can be installed in places with a maximum temperature of 35 ° C and offers a service life of more than 50,000 hours to operate at 25 ° C. It works with a power supply and 220-240 V and can be installed by recessed, its dimensions are 110 mm x 230 mm diameter and its weight is 1.3 kg This is a type of downlight for general lighting technical and is a luminaire designed to provide general lighting with high performance lighting to create uniform and very comfortable spaces. It is, therefore, the perfect combination of design and visual comfort. This type of downlight is perfect for restaurants and hospitals, as they are rooms in which you can notario its benefits.

APPLICATION

General technical lighting

PACKAGING CONTENTS

1 Unit

TECHNICAL INFORMATION

FREQUENCY

50 Hz

DRIVER INCLUDED

Yes

LIGHTING EFFICIENCY (LM/W)

96 lm/W

IP RATING

IP20

ELECTRICAL CLASS

type 1

LUMENS (LM)

2300 lm

OPERATING TEMPERATURE RANGE (°C)

35 °C maximum

INTEGRATED POWER SUPPLY

Yes

LUMENS/W

2300 lm/24W

POWER SUPPLY (V~)

220/240 V~

L70 (°C)

100,000 h at 25 °C

OPTICS

Medium

COLOR TEMPERATURE (K)

3000 K

L90 (°C)

50,000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

CONTROL

1-10 V

LIGHT BEAM APERTURE ANGLE (°)

65°

POWER (W)

24 W

CRI

80


COLOR TYPE

WW

SERVICE LIFE

50.000 h

CHROMATICS CRI ICONS



INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Ceiling surface mount

INSTALLATION TYPE

Flush mount

MINIMUM INSTALLATION HEIGHT

150

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Quick connector

REGULATIONS

WARRANTY

5 years 50,000 h

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053136232

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053136232

PACKAGING VOLUME

9811125

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

135

PACKAGING GROSS WEIGHT

1.5

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

285

PACKAGING NET WEIGHT

1.2

UNITARY PACKAGING GROSS
WEIGHT

1.5

PACKAGING LENGTH

255

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

1.2