

Spotlight 615 rail 4000 K Flood black

REF. 61500038-384



BASIC INFORMATION

APPLICATION

Accent lighting

PACKAGING CONTENTS

1 unit

ETIM CLASS

EC001744

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

CRI

80

LIGHTING EFFICIENCY (LM/W)

100 lm/W

IP RATING

IP20

DIRECTIONAL

Yes

LUMENS (LM)

2500 lm

OPERATING TEMPERATURE RANGE (°C)

35 °C maximum

DRIVER INCLUDED

Yes

LUMENS/W

2500lm/ 25W

POWER SUPPLY (V~)

230 V~

L70 (°C)

100,000 h at 25 °C

OPTICS

Flood

COLOR TEMPERATURE (K)

4000 K

L90 (°C)

50,000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

CONTROL

On/Off

COLOR TYPE

NW

POWER (W)

25 W

CHROMATICS CRI ICONS

CRI
80

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

3-phase adjustable rail

REGULATIONS

WARRANTY

5 years

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053198698

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0.846

PRODUCT NET WEIGHT

0.635

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053198698

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

84

PACKAGING WIDTH

177

PACKAGING LENGTH

296

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

4400928

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.846

PACKAGING NET WEIGHT

0.635

PACKAGING WEIGHT UNIT

KGM