# Customisable kit with cover and fin, 3 schuko socket outlets and 2 empty elements black S400 Indesk

REF. **45503000-138**



# BASIC INFORMATION

## DESCRIPTION

In black colour, the kit is part of the table customizable with cover and fin metal, 3 sockets of plugs SCHUKOS and 2 empty elements of the Simon series, it is suitable to be flush mounted in furniture. This element has a dielectric strength with no holes or contours with 2000 V at 50H during a minute and a insulation resistance > 5 M? at 500 V. Its current is 16 A current and a voltage of 250 V ~. It has dimensions of 295 x 185 x 85 mm and a connector is figure Wieland ® gst18i with 3 poles male in-line with patch cord of 22 cm It is a very resistant product to knocks and safe in case of fire designed with enclosure painted steel, profile in anodised aluminium, covers and fastenings in self-extinguishing thermoplastic and halogen-free. Simon recommends that to complete the installation of the product must be combined with the functions of the range 400.

## FINISH

Black

## MATERIAL

Metal

## COMPATIBILITY

Functions of the Simon 400 range, combinable with the Simon Electric Cabling range.

## PACKAGING CONTENTS

Pre-wired profile, enclosure, fastening claws and installation manual.

## ETIM CLASS

EC002759

## REMARKS

To complete the product installation combine it with the Simon 400 functions (refs. 400XXXXX-03X).

# TECHNICAL INFORMATION

### AVAILABLE MARKET
CE

### PROTECTION AGAINST DIRECT ACCESS OF CONTACTS
No

### PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS
Yes, thanks to the included protective cover and cable outlet with metal fin

### DIELECTRIC STRENGTH
No holes or contours, with 2000V at 50 Hz for 1 minute

### MAX TEMP DURING CONSTRUCTION WORK (°C)
+60°C

### NUMBER OF POSSIBLE ELEMENTS
2

### FORMAT
Schuko

### HEAT RESISTANCE (°C)
+70°C (according to standard IEC 60670)

### INSULATION RESISTANCE (V-MΩ)
>5 M? at 500 V

### CURRENT (A)
16 A

### IP RATING
IP30

### MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 at +60° C

### NOMINAL VOLTAGE (V~)
250 V~

### TYPE OF POWER SUPPLY CONNECTOR
Wieland® GST 18i male 3-pole overhead connector with 22 cm patch cord

### RAL
9005

### NUMBER OF REAR ENTRANCES
2

### RECESS DIMENSION (MM)
273 x 175 mm (± 2mm)

### NUMBER OF SOCKETS
3 sockets for standard current circuit

### VERSION
5 elements

## INSTALLATION AND MAINTENANCE

### CABLING ACCESS
With metal fin

### CLAW RANGE OF OPERATION (MM)
Between 20 and 40 mm

### REMOVAL OF COMPONENTS

### NUMBER OF COVER OPENING POSITIONS
1

### EXTINGUISHING (°C)
+70 °C (according to standard IEC 60670)

### TYPE OF FASTENING
By lateral tightening of claws provided with the enclosure. Optional possibility to fasten the enclosure with screws through the provided holes in the sides of the enclosure chassis.

### REMOVAL OF THE FRAME
Only with tool

### INSTALLATION TYPE
Suitable for recessed mount in furniture.

### OPENING ORIENTATION
At 45

### REMOVAL OF THE PLATE
Only with tool

### SECURING POSSIBILITIES
Using supplied claws or screws in the available holes

### MOUNTING WITHOUT ACCESSORIES
Supplied with all necessary materials for installation.

## REGULATIONS

### REGULATIONS
Directiva 2014/35/UE LVD;Directiva 2011/65/UE RoHS;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;IEC 60884-1 Ed 3.2;

## LOGISTICS INFORMATION

UNITARY EAN CODE
8421053085424

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
2.15

PRODUCT NET WEIGHT
2.15

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053085424

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
320

PACKAGING WIDTH
195

PACKAGING LENGTH
90

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
6405750

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0

PACKAGING NET WEIGHT
2.15

PACKAGING WEIGHT UNIT
KGM