

Thermostat for electric underfloor heating Simon iO with included probe gloss white Simon 100

REF. 10000811-130



BASIC INFORMATION

FINISH

Gloss white

MATERIAL

Various

PACKAGING CONTENTS

Mechanism and instructions

ETIM CLASS

EC003263

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CURRENT (A)

10 A

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

CABLE SECTION ADMITTED (MM)

From 1,5 to 2,5 mm

CONNECTIVITY PROTOCOL

Z-wave

POWER SUPPLY (V~)

127/230 V~

NUMBER OF POSSIBLE ELEMENTS

1 element

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

INDICATOR FUNCTION

No

INSTALLATION AND MAINTENANCE

CLAW

INSTALLATION DIRECTION

Vertical

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Screw

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal

INSTALLATION TYPE

Suitable for recess

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053217467

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0.33

PRODUCT NET WEIGHT

0.33

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053217467

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

75

PACKAGING WIDTH

105

PACKAGING LENGTH

127

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

1000125

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.329

PACKAGING NET WEIGHT

0.33

PACKAGING WEIGHT UNIT


KGM



Instalación centralizada para caldera/bomba de calor
Centralized installation for boiler/heat pump



Instalación suelo radiante eléctrico
Installation with electric floor



Instalación zonificada a 230V con contacto Normalmente Abierto
230V installation with Normally Open contact

Para información más detallada consultar la hoja de instrucciones
For more detailed information check the instruction sheet