

Voice and data flat plate with dust cover for 1 element for 1 Nexans® RJ45 connector white Simon K45

REF. KA85/9



BASIC INFORMATION

DESCRIPTION

The range of housings for Voice and Data transmission of Simon, through its Simon K45 range, is prepared for the future, with the technological changes that require agility, functionality and convenience. The option of integration into the same housing for electrical, voice, data, audiovisual, multimedia, and control, is linked to the possibility of connection with the most renowned brands on the market. Its absolute compatibility, both in copper and fibre optics, help to resolve in a practical, simple and immediate way, all connectivity problems in your office, meeting room or conference room. Connectors and plates for voice and data connections. It is a flat voice and data plate with dust cover with 1 element, compatible for 1 Nexans ® RJ45 connector Finished in white Simon K45 compatible with the Nexans ® RJ45 Connectors. Placement Individual. Plate for 1 and 2 RJ45 connectors. When combining the voice and data plate in vertical housing (mini columns, columns, Teleblock, mechanism holder trunking) you must use the 90° positioner (ref. K66) to guide the plate into a vertical position. Dimensions 45 x 45 mm x 8.5 mm Halogen-free thermoplastic that guarantees no flame propagation in case of fire and low toxicity in case of smoke complies regulation UNE-EN 60670-1: 2006. Suitable for surface mounting and flush mounting. Resistant to corrosion and extreme temperatures (-5 to 60 °C). Do not use abrasive cloths and / or abrasive cleaners containing chlorine.

FINISH

White

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-030)

PACKAGING CONTENTS

Flat voice and data plate with dust cover

ETIM CLASS

EC000018

REMARKS

When combining the voice and data plate in vertical housings (mini columns, columns, Teleblock, channels, mechanism holders, etc.) you must use the 90° positioner (ref. K66) to guide the plate into a vertical position.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST SHUTTER

Yes

NUMBER OF MODULES

Four

AVAILABLE IN

Plate for 1 and 2 RJ45 connectors

FORMAT

RJ45

PLATE TYPE

Flat

COMPATIBLE WITH CONNECTORS

Nexans® LANmark®-5 EVO, LANmark®-6 EVO.

IP RATING

IP20

RAL

9003

KIT AVAILABILITY

No

RJ45 ADAPTOR MODULE

Included in voice and data plate

RJ45 CONNECTORS

Not included in voice and data plate

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT RJ45 PLATES

Nexans® RJ45 connectors

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

SNAP-FIT TYPE

Nexans® RJ45 connectors

DUST PROTECTION

Yes

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

VERSION

Single

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-030)

INSTALLATION DIRECTION

Vertical according to the direction of the mechanisms

INSTALLATION TYPE

Suitable for surface and flush mounting

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.007

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

4140000

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8426436046948

PACKAGING VOLUME UNIT

DMQ

UNITARY PACKAGING VOLUME

0.3

UNITS CONTAINED PACKAGING

20

PACKAGING GROSS WEIGHT

0.14

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING HEIGHT

90

PACKAGING NET WEIGHT

0.14

UNITARY PACKAGING GROSS WEIGHT

0.007

PACKAGING WIDTH

200

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

230