

Bottom closure for Teleblock telescopic profiles with manual elevation Simon K45

REF. KTLA6



BASIC INFORMATION

DESCRIPTION

It is a bottom closure designed for Teleblock telescopic profiles with manual elevation included in the series Simon K45. This collection was created with the aim of facilitating the workplace solutions in the work stations. To do this, it has a series of solutions to be installed easily and quickly, raising the connections to the highest level. These solutions of the series Simon K45 stand out, in addition, due to be perfectly into the furniture. This product measures 102 x 59 x 23 mm and is finished in black. Also, is made of thermoplastic material and self-extinguishing halogen-free, designed to guarantee no flame spread in case of fire of a fire. The same way, ensuring the low toxicity in case of smoke. For optimum preservation of this article, it is recommended to install it in environments with a temperature range between -5 and 60 ° C

FINISH

Black

MATERIAL

Plastic

COMPATIBILITY

Teleblock with manual elevation from the Simon K45 range.

PACKAGING CONTENTS

Bottom closure for telescopic profiles with manual elevation.

ETIM CLASS

EC002649

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DIELECTRIC STRENGTH

Without perforation or
contournement with 2000 V at
50H during 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

HEAT RESISTANCE (°C)

+70°C (according to standard IEC
60670)

INSULATION RESISTANCE (V-MΩ)

>5 MOhm at 500 V

IP RATING

IP4X

KIT AVAILABILITY

No

LINKABLE

No

MAINTENANCE

Clean with a soft, dry cloth. Do
not use abrasive cloths or
cleaning products that contain
chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

RAL

7021

INSTALLATION AND MAINTENANCE

CABLING ACCESS

Through the space enabled in
the lower part of the profile.

EXTINGUISHING (°C)

+850 °C (according to standard
IEC 60670)

TYPE OF FASTENING

Using the thread on the screws
that ensures closure on the
Simon K45 Teleblock telescopic
profile. Note: this article is a
replacement part and is supplied
with the Simon K45 Teleblock
telescopic profile.

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + Directive 2011/65/UE RoHS + EN 50581:2012 + EN 60670-1:2005

LOGISTICS INFORMATION

UNITARY EAN CODE

8426436056558

PRODUCT NET WEIGHT

0.055

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

0.3

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8426436056558

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

0.045

UNITARY PACKAGING VOLUME

0.3

PACKAGING HEIGHT

59

PACKAGING NET WEIGHT

0.055

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

66

PACKAGING WEIGHT UNIT

KGM

UNITARY PACKAGING GROSS WEIGHT

0.055

PACKAGING LENGTH

105