

Downlight 725.23 Flush mount WW General IP44 White

REF. 72523930-983



BASIC INFORMATION

DESCRIPTION

Downlight of the series Simon 725.33 with General optics and whose installation is by recessed. Its white finish makes it a type of downlight perfect for any type of room and decoration and has dimensions of 165 x 51 mm and a weight of just 500 g. It can be installed in places with a temperature located between the -15 and 40°C and offers a service life of a 30,000 hours, approximately, operating at 25 ° C. It has a frequency of details of 50 / 60 Hz and its power supply is 100-240 V and its control is performed by On / Off. Its colour temperature is of 3100 K and has a light intensity of 1200lm / 14W. This type of downlights of the series 725 are perfect for general lighting, above all, restaurants and hospitals and they are ideal for creating uniform lighting, offering a high visual comfort in transit areas and also in offices, restaurants or hospitals.

APPLICATION

General lighting

PACKAGING CONTENTS

1 unit

ETIM CLASS

EC001744

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

DRIVER INCLUDED

Yes

LUMENS (LM)

1200 lm

IP RATING

IP44

ELECTRICAL CLASS

Type 1

LUMENS/W

1200 lm/14W

OPERATING TEMPERATURE RANGE (°C)

-15 - 40 °C

INTEGRATED POWER SUPPLY

Yes

OPTICS

General

POWER SUPPLY (V~)

100/240 V~

L70 (°C)

30,000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

COLOR TEMPERATURE (K)

3100 K

LIGHT BEAM APERTURE ANGLE (°)

120°

POWER (W)

14 W

CONTROL

On/Off

COLOR TYPE

WW

SERVICE LIFE

30.000 h


CRI

80

LIGHTING EFFICIENCY (LM/W)

86 lm/W

CHROMATICS CRI ICONS



INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Surface

INSTALLATION TYPE

Flush mount

MINIMUM INSTALLATION HEIGHT

101

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Quick connector

REGULATIONS

WARRANTY

3 years 30,000 h

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0.616

PRODUCT NET WEIGHT

0.616

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053116883

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

80

PACKAGING WIDTH

195

PACKAGING LENGTH

195

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

3.042

PACKAGING VOLUME UNIT

DMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

0.616

PACKAGING WEIGHT UNIT

KGM