

**Adjustable floor box kit for concrete floor 8 elements with
2 double sockets, 1 double UPS socket and 2 plates with 1
RJ45 Cat.6A FTP connector grey Simon 500 Cima**

REF. 52007401-030



BASIC INFORMATION

DESCRIPTION

From the Simon 500 Cima series comes this with adjustable floor box kit for concrete floor and 8 elements with 2 double sockets, 1 double UPS socket and 2 plates with 1 RJ45 Cat.6A FTP connector. In the format French-Belgian socket and snap-fit RJ45 Keystone I, II, ATT ® / Avaya ®. Finished in grey, with 2 double sockets for standard current circuit. When installing mounted, keep in mind that it has a click terminal connection (1 click ®). To complete a successful installation of this product, it must be combined with a plastic tray (reference 52052104-035). Optionally, we recommend combining it with the flush-mount trim cover (reference 52053104-035) in cases where you do not install the same floor covering. This kit is specially designed and designed for assembly in concrete floor, although it is also suitable for installation in raised floor. Manufactured with different metal materials that have properties self-extinguishing and halogen-free. In case of fire, you will get the maximum protection.

FINISH

Grey

COMPATIBILITY

Simon 500 CIMA mechanisms

MATERIAL

Plastic

ETIM CLASS

EC000024

REMARKS

To complete the installation of the product, it must be combined with a plastic tray (ref.52052104-035) or with a metal tray (ref.52052204-033). Alternatively, it may be combined with flush-mount trim cover (ref.52053104-035) in cases where the same floor lining is not installed.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

PROTECTION AGAINST DIRECT ACCESS OF CONTACTS

Yes

NUMBER OF CLAMP-HOLDER HOLES

8

NUMBER OF CONNECTORS

2

CONNECTOR TYPE

6A FTP

DUST SHUTTER

Yes

FORMAT

French-Belgian

IK CLASSIFICATION

08

INDICATOR FUNCTION

Yes

CURRENT (A)

16 A

IP RATING

IP4X

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

PLATE TYPE

Flat

RAL

7011

RECESS DIMENSION (MM)

170 x 265 mm

NUMBER OF UPS SOCKET OUTLETS

1

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

0

NUMBER OF COVER OPENING POSITIONS

2

EXTINGUISHING (°C)

+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-2-11)

REMOVAL OF THE FRAME

Only with tool

CAN BE INSTALLED IN TRAY

Plastic and metallic

INSTALLATION DIRECTION

Horizontal, Vertical

REMOVAL OF THE PLATE

Only with tool

REMOVAL OF THE SOCKET

Only with tool

TYPE OF TERMINAL CONNECTION - FUNCTION 1

1 click connection (1 click®)

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053112311

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053112311

PACKAGING VOLUME

3933900

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

75

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

186

PACKAGING NET WEIGHT

2.2

UNITARY PACKAGING GROSS
WEIGHT

2.2

PACKAGING LENGTH

282

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

2.2