# On-desk set with 2 German socket outlets, 2 UPS sockets and plate for 4 RJ45 connectors aluminium Simon 400

REF. **42602240-133**



## BASIC INFORMATION

### DESCRIPTION

Unified in the minimum space all the functions, with the kit of desk top of Simon 400. With a compact design of clean lines and finishes in aluminium, this kit consists of 2 Schuko socket outlets, 2 UPS (uninterruptable power supplies) and a plate with 4 RJ45 connectors, a greater number of functions in a reduced space to optimize its working area. Recessed and installation manual elevation, it is compatible with a voltage of 250 V of power and 16 A of intensity, connected to figure Wieland, and with connectors compatible with Keystone ports. Moreover, its dielectric strength is 2000 V at 50H per minute and has a insulation resistance > 5 M? at 500 V. Made from aluminium profile and covers and fastenings in self-extinguishing thermoplastic and halogen-free, protects the flame spread and toxicity by smoke, in case of fire. Innovation and functionality that optimizes space with Simon 400.

### FINISH

Aluminium

### MATERIAL

Metal

### COMPATIBILITY

Can be combined with the range of Electric Cabling from Simon.

### PACKAGING CONTENTS

Pre-wired profile, table-top supports, rear trim cover and installation manual.

## TECHNICAL INFORMATION

### AVAILABLE MARKET
CE

### DIELECTRIC STRENGTH
No holes or contours, with 2000V at 50 Hz for 1 minute

### MAX TEMP DURING CONSTRUCTION WORK (°C)
+60°C

### FORMAT
Schuko

### HEAT RESISTANCE (°C)
+70°C (according to standard IEC 60670)

### INSULATION RESISTANCE (V-MΩ)
>5 M? at 500 V

### CURRENT (A)
16 A

### IP RATING
IP30

### MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 at +60° C

### NOMINAL VOLTAGE (V~)
250 V~

### TYPE OF POWER SUPPLY CONNECTOR
Wieland® GST 18i male 3-pole overhead connector with 22 cm patch cord

### RAL
9006

### NUMBER OF RJ45 WINDOWS
4

### SNAP-FIT RJ45 PLATES
Keystone® I, II and Systimax®

### SNAP-FIT TYPE
Keystone® I, II and Systimax®

### NUMBER OF SOCKETS
2 sockets for standard current circuit and 2 sockets for stable current circuit (UPS)

### NUMBER OF UPS SOCKET OUTLETS
2

### VERSION
6 elements

## INSTALLATION AND MAINTENANCE

### CLAW RANGE OF OPERATION (MM)
Between 16 and 40 mm

### EXTINGUISHING (°C)
+70 °C (according to standard IEC 60670)

### TYPE OF FASTENING
By tightening existing clamps in the fastening bracket.

### INSTALLATION TYPE
Suitable for fixing to furniture.

### SECURING POSSIBILITIES
Using clips included in the fastening brackets

### MOUNTING WITHOUT ACCESSORIES
Supplied with all necessary materials for installation.

## REGULATIONS

### REGULATIONS

Directiva 2014/35/UE LVD;Directiva 2011/65/UE RoHS;EN 50173-1:2011;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;IEC 60884-1 Ed 3.2;

## LOGISTICS INFORMATION

### UNITARY EAN CODE
8421053196052

### UNITARY PACKAGING HEIGHT
0

### UNITARY PACKAGING WIDTH
0

### UNITARY PACKAGING LENGTH
0

### UNITARY PACKAGING VOLUME
0

### UNITARY PACKAGING GROSS WEIGHT
1.2

### PRODUCT NET WEIGHT
1.2

### UNITARY PACKAGING WEIGHT UNIT
KGM

### PACKAGING EAN
8421053196052

### UNITS CONTAINED PACKAGING
1

### PACKAGING HEIGHT
330

### PACKAGING WIDTH
125

### PACKAGING LENGTH
95

### PACKAGING MEASUREMENT UNIT
MMT

### PACKAGING VOLUME
3918750

### PACKAGING VOLUME UNIT
MMQ

### PACKAGING GROSS WEIGHT
0

### PACKAGING NET WEIGHT
1.2

### PACKAGING WEIGHT UNIT
KGM