# Complete kit with cover, metal fin, 2xUSB charger and 3 schuko socket outlets black S400 Indesk

REF. **45423000-138**



## BASIC INFORMATION

### DESCRIPTION

The Simon 400 Indesk series is designed to provide solutions for the most demanding environments. Thanks to this series, we will have all the necessary connections at our fingertips without annoying cables on the floor. A complete kit with a cover and fin, created for flush mounting in the table, has the capacity for a charger 2 x USB and 3 schuko socket bases in black. It supports 250 volts and 16 amps of current. Its connection is made via a Wieland® gst18i three-pole male aerial connector with a 22-centimeter patch cord. Manufactured with high-quality materials that provide this piece with great resistance, an example of this is its painted steel enclosure, its anodized aluminum profile, and its covers and fittings made of self-extinguishing thermoplastic free of halogens.

### FINISH

Black

### MATERIAL

Metal

### COMPATIBILITY

Can be combined with the range of Electric Cabling from Simon.

### PACKAGING CONTENTS

Pre-wired profile, enclosure, fastening claws and installation manual.

### ETIM CLASS

EC002759

## TECHNICAL INFORMATION

### AVAILABLE MARKET
CE

### PROTECTION AGAINST DIRECT ACCESS OF CONTACTS
No

### PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS
Yes, thanks to the included protective cover and cable outlet with metal fin

### DIELECTRIC STRENGTH
No holes or contours, with 2000V at 50 Hz for 1 minute

### MAX TEMP DURING CONSTRUCTION WORK (°C)
+60° C

### FORMAT
Schuko

### HEAT RESISTANCE (°C)
+70°C (according to standard IEC 60670)

### INSULATION RESISTANCE (V-MΩ)
>5 MΩ a 500 V

### CURRENT (A)
16 A

### IP RATING
IP30

### MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 to 60° C

### NOMINAL VOLTAGE (V~)
250 V~

### TYPE OF POWER SUPPLY CONNECTOR
Wieland® GST 18i male 3-pole overhead connector with 22 cm patch cord

### RAL
9005

### RECESS DIMENSION (MM)
228 x 175 mm (± 2mm)

### NUMBER OF SOCKETS
3 sockets for standard current circuit

### NUMBER OF USB CHARGERS
1

### VERSION
4 elements

## INSTALLATION AND MAINTENANCE

### CABLING ACCESS
With metal fin

### CLAW RANGE OF OPERATION (MM)
Between 20 and 40 mm

### NUMBER OF COVER OPENING POSITIONS
1

### EXTINGUISHING (°C)
+70 °C (according to standard IEC 60670)

### TYPE OF FASTENING
By tightening existing clamps in the fastening bracket.

### REMOVAL OF THE FRAME
Only with tool

### INSTALLATION TYPE
Suitable for recessed mount in furniture.

### OPENING ORIENTATION
At 45°

### SECURING POSSIBILITIES
Using supplied claws or screws in the available holes

### MOUNTING WITHOUT ACCESSORIES
Supplied with all necessary materials for installation.

## REGULATIONS

### REGULATIONS

Directiva 2014/35/UE LVD;Directiva 2011/65/UE RoHS;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;IEC 60884-1 Ed 3.2;

## LOGISTICS INFORMATION

### UNITARY EAN CODE
8421053273623

### UNITARY PACKAGING HEIGHT
0

### UNITARY PACKAGING WIDTH
0

### UNITARY PACKAGING LENGTH
0

### UNITARY PACKAGING MEASUREMENT UNIT
MMT

### UNITARY PACKAGING VOLUME
0

### UNITARY PACKAGING VOLUME UNIT
MMQ

### UNITARY PACKAGING GROSS WEIGHT
1.905

### PRODUCT NET WEIGHT
1.905

### UNITARY PACKAGING WEIGHT UNIT
KGM

### PACKAGING EAN
8421053273623

### UNITS CONTAINED PACKAGING
1

### PACKAGING HEIGHT
90

### PACKAGING WIDTH
187

### PACKAGING LENGTH
250

### PACKAGING MEASUREMENT UNIT
MMT

### PACKAGING VOLUME
4207500

### PACKAGING VOLUME UNIT
MMQ

### PACKAGING GROSS WEIGHT
0

### PACKAGING NET WEIGHT
1.905

### PACKAGING WEIGHT UNIT
KGM