

## Brightness sensor recessed box KNX squared white IP20

REF. 89262720-230



### BASIC INFORMATION

#### DESCRIPTION

Embedded light detector. The recommended installation height is 2.8 m, with a maximum height of 4 m. The light regulation range is 2 - 1000 lux. The detector configuration is done via remote control and KNX. It features TEACH operating mode. Possibility of interconnection between sensors via KNX. The control protocol is KNX. The power supply voltage is KNX (21 - 30 VDC). The detector's operating temperature is: -20 - 50 °C. Black finish, IP 54 protection grade, and dimensions: 94 x 94 x 51 mm. 5-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

#### FINISH

White

#### COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

#### ETIM CLASS

EC000927

## TECHNICAL INFORMATION

### IP RATING

IP20

### RAL

9003

### POWER SUPPLY (V~)

220/240 V~

### CONTROL

On/Off

## INSTALLATION AND MAINTENANCE

### MINIMUM INSTALLATION HEIGHT

2.3

## LOGISTICS INFORMATION

### UNITARY EAN CODE

8421053401613

### UNITARY PACKAGING HEIGHT

0

### UNITARY PACKAGING WIDTH

0

### UNITARY PACKAGING LENGTH

0

### UNITARY PACKAGING MEASUREMENT UNIT

MMT

### UNITARY PACKAGING VOLUME

0

### UNITARY PACKAGING VOLUME UNIT

MMQ

### UNITARY PACKAGING GROSS WEIGHT

0.207

### PRODUCT NET WEIGHT

0.117

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING EAN

8421053401613

### UNITS CONTAINED PACKAGING

1

### PACKAGING HEIGHT

90

### PACKAGING WIDTH

124

### PACKAGING LENGTH

160

### PACKAGING MEASUREMENT UNIT

MMT

### PACKAGING VOLUME

2325323

### PACKAGING VOLUME UNIT

MMQ

### PACKAGING GROSS WEIGHT

0.207

### PACKAGING NET WEIGHT

0.117

### PACKAGING WEIGHT UNIT

KGM