

DALI downlight 735.21 WW Medium Black

REF. 73521338-683



BASIC INFORMATION

APPLICATION

Accent lighting, General lighting

PACKAGING CONTENTS

1 unit

ETIM CLASS

EC001744

TECHNICAL INFORMATION

IP RATING

IP20

DRIVER INCLUDED

Yes

LUMENS/W

2200 lm/22W

OPERATING TEMPERATURE RANGE (°C)

Max. temp.: 35°C

L70 (°C)

50,000 h

OPTICS

Medium

COLOR TEMPERATURE (K)

3000 K

L90 (°C)

50,000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

CONTROL

DALI

COLOR TYPE

WW

POWER (W)

22 W

CRI

80

LIGHTING EFFICIENCY (LM/W)

100 lm/W

SERVICE LIFE

50.000 h

LUMENS (LM)

2200 lm

INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Surface-mounted

INSTALLATION TYPE

Flush-mounted

REGULATIONS

WARRANTY

5 years

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053285428

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

1.5

PRODUCT NET WEIGHT

1.2

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053285428

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

135

PACKAGING WIDTH

285

PACKAGING LENGTH

255

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

9811125

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

1.5

PACKAGING NET WEIGHT

1.2

PACKAGING WEIGHT UNIT

KGM