# Kit Flash 90 schuko power socket with "retractable cover", USB Type C Dock including 2x HDMI+LAN+3x USB Type A, USB charger Type C 20W and grommet (cable outlet) white Simon 400

REF. **43333301-130**




## BASIC INFORMATION

### DESCRIPTION

Kit Flash 90 based on a retractable schuko power socket-outlet for installation in furniture with an optional protective lid to allow it to be closed and hide the connections when not in use. Includes a USB Type-C dock with 2 HDMI outputs for display, 1 Gigabit Ethernet port, and 3 USB Type-A connectors for keyboard, mouse, and any other connection device based on the USB Type-A connector. The kit includes a 20W USB Type-C charger and a cable outlet in a white finish. Supplied with a 20cm long patch cord terminated with a 3-pole Wieland® Gst18i male overhead quick connector with a safety anchor for easy connection and disconnection from the mains safely without interrupting the power supply. The kit is supplied assembled with the internal connections pre-made. It is only necessary to make the die in the furniture where the product will be fixed and once done, connect it to the mains for it to be functional. It requires ordering the dock power supply separately (ref. CR6100121150201/14)

### FINISH

White

### MATERIAL

Plastic

### ETIM CLASS

EC002759

## TECHNICAL INFORMATION

### AVAILABLE MARKET
CE

### PROTECTION AGAINST DIRECT ACCESS OF CONTACTS
Yes

### PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS
Socket with retractable cover to avoid access of dust and small objects when are not in used

### RJ45 CONNECTORS
Yes

### CONNECTOR TYPE
Schuko

### NUMBER OF CONTACTS
3

### FORMAT
Schuko

### CURRENT (A)
16 A

### IP RATING
IP20

### MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### NOMINAL VOLTAGE (V~)
250 V~

### RAL
9003

### RECESS DIMENSION (MM)
ø80 mm

### RJ45 ADAPTOR MODULE
Yes

### SNAP-FIT RJ45 PLATES
Directly to the Dock

### SNAP-FIT TYPE
Embedded in the dock

### USB CHARACTERISTICS
Charging

### USB CURRENT (A)
2,2 A

### POWER DELIVERY USB
Yes

### QUICK CHARGE USB
Yes

### USB VOLTAGE (V~)
9 V~

### VOLTAGE (V~)
250 V~

## INSTALLATION AND MAINTENANCE

### REMOVAL OF COMPONENTS
No tools needed

### REMOVAL OF COVER
Only with tool

### EXTINGUISHING (°C)
+650 °C (according to standard IEC 60670)

### TYPE OF TERMINAL CONNECTION - FUNCTION 1
Quick connector

## REGULATIONS

### REGULATIONS

Dir. 2014/35/UE LVD*1 | Dir. 2014/30/UE EMC*3 |Dir. 2011/65/UE RoHS + post. mod.*1 | Dir. 2009/125/EC ErP (Reg. UE 2019/1782) *1 *13 *12 | S.I. 2016 No. 1101 - The Electrical Equipment (Safety) Regulations 2016*2 | S.I. 2012 No. 3032 - The Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2012*2 | IEC 60884-1 Ed.3.2*1 | BS 1363-2:2016+A1:2018*2 | UNE 20315-1-1:2017*5 | BS 1363-4:2016+A1:2018*2 | UNE 20315-1-2:2017*5 | DS 60884-2-D1:2023*4 | CEI 23-50 V4*7 | SANS 164-1:2021*6 | SN 441011-2-1:2019*9 | SI 32 Fig. 204 B*8 | AS/NZS 3112:2017*11 | EN 50173-1:2018*10 | EN 50563:2011 + A1:2013*13 *12 | EN 55032:2015 + A11:2020 + A1:2020*12*14 *16 | EN 62368-1: 2014 + A11:2017*13 *12 | EN 55035:2017 + A11:2020*12*14 *16 | ETSI-EN 301489-34 V2.1.1*13 | EN IEC 61000-3-2:2019 + A1:2021 + A2:2024*12 *16 | EN IEC 60670-1:2021+ A11:2021*15 | EN 61000-3-3:2013 +A1:2019 + A2:2021 *12 *16 | EN IEC 63000:2018

## LOGISTICS INFORMATION

### UNITARY EAN CODE
8421053397886

### UNITARY PACKAGING HEIGHT
0

### UNITARY PACKAGING WIDTH
0

### UNITARY PACKAGING LENGTH
0

### UNITARY PACKAGING MEASUREMENT UNIT
MMT

### UNITARY PACKAGING VOLUME
0

### UNITARY PACKAGING VOLUME UNIT
MMQ

### UNITARY PACKAGING GROSS WEIGHT
0.211

### PRODUCT NET WEIGHT
0.192

### UNITARY PACKAGING WEIGHT UNIT
KGM

### PACKAGING EAN
8421053397886

### UNITS CONTAINED PACKAGING
1

### PACKAGING HEIGHT
120

### PACKAGING WIDTH
130

### PACKAGING LENGTH
252

### PACKAGING MEASUREMENT UNIT
MMT

### PACKAGING VOLUME
3931200

### PACKAGING VOLUME UNIT
MMQ

### PACKAGING GROSS WEIGHT
0.793

### PACKAGING NET WEIGHT
0.192

### PACKAGING WEIGHT UNIT
KGM