

Waterproof linear luminaire BT Mesh 42W 4000K with detector 10m HF+LUX and emergency IP65

REF. 89362600-424



BASIC INFORMATION

DESCRIPTION

Watertight luminaire with integrated HF detector, with emergency function and bluetooth connectivity. The power is 42 W, the luminous flux is 5940 lm, and the color temperature is 4000 K. The emergency mode duration is 3 hours according to standard EN 60598-2-22.

The maximum installation height is 4m and the installation is surface-mounted. The detection range is 10m and the detection angle is 360°.

The brightness regulation range is 2 - 2000 lux and the timing range is 5 s - 60 min.

The luminaire configuration is done via a bluetooth application. Possibility of interconnection between luminaires via bluetooth mesh.

The power supply voltage is 220 - 240 VAC. The operating temperature is: -20 - 40 °C.

Protection rating IP 65 and IK 07. Dimensions: 1500 x 87 x 58 mm.

5-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

ETIM CLASS

EC002892

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

IP RATING

IP65

IK CLASSIFICATION

07

POWER SUPPLY (V~)

220/240 V~

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053401583

UNITARY PACKAGING GROSS WEIGHT

2.625

PACKAGING LENGTH

1690

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

2.193

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

2325323

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8421053401583

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

2.625

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

80

PACKAGING NET WEIGHT

2.193

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

100

PACKAGING WEIGHT UNIT

KGM