

Trim plate for MCB or DIN format RCCB for 3 elements white Simon K45

REF. KF03/9



BASIC INFORMATION

DESCRIPTION

Trim plate for miniature circuit breaker or residual current circuit breaker, DIN format of 3 elements, white in colour finish and belonging to the series Simon K45. The range K45 SImon, in addition to socket-outlets, has floor boxes, Teleblock, wall-mounted boxes, watertight floor boxes, IP55, mini-columns, columns and ofiblock (Plus, Compact and Line) so that it can use it in the different electrical installations in your home. This plate has dimensions of 135 x 45 x 44 mm and it is suitable both for surface-mounted or to be flush mounted, in places with a temperature located between -5 to 60 ° C, although it is able to withstand extreme temperatures and high. Complies with the regulation European UNE -s 60670-1: 2006 and is manufactured in halogen-free thermoplastic material, which guarantees the no-propagation of the flame (in case of fire and low toxicity (in the event of smoke generation). To clean this plate, you can do it is very simple, as it will only need to wipe it with a soft and dry cloth and never use abrasive cloths or cleaners that contain chlorine in its formula.

FINISH

White

MATERIAL

Plastic

COMPATIBILITY

Simon K45 housing for mounting on the wall, floor, ceiling and furniture.

PACKAGING CONTENTS

Plate and adaptor for MCB or residual current circuit breaker, DIN format

ETIM CLASS

EC001024

REMARKS

Protection element not included (must be purchased separately). In the event of using another brand for elements of protection, the plate is compatible with any element of protection in DIN format of thickness no greater than 45 mm.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

AVAILABLE IN

Versions with two-pole MCB 10A, 16A and residual current circuit breaker 25A with sensitivity of 30 mA

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

FORMAT

DIN

INDICATOR FUNCTION

No

IP RATING

IP20

KIT AVAILABILITY

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

NUMBER OF MODULES

1 and a half modules

RAL

9003

VERSION

Single

INSTALLATION AND MAINTENANCE

TYPE OF FASTENING

Fixing by direct snap-fit, no tools needed

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-030)

INSTALLATION DIRECTION

Vertical according to the direction of the mechanisms

INSTALLATION TYPE

Suitable for surface and flush mounting

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + Directive 2014/30/UE EMC + Directive 2011/65/UE RoHS + EN 50581:2012 + EN 60898-1:2003 + EN 60898-1:2003 A1:2004 + EN 60898-1:2003 A11:2005 + EN 60898-1:2003 A12:2008 + EN 60898-1:2003 A13:2012 + EN 61008-1:2012 + EN 61008-1:2012 A1:2014 + EN 61008-1:2012 A2:2014 + EN 61008-1:2012 A11:2015 + EN 61008-2-1:1994 + EN 61008-2-1:1994 A11:1998 + EN 61543:1995 + EN 61543:1995 A11:2003 + EN 61543:1995 A12:2005 + EN 61543:1995 A2:2006

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.046

PACKAGING MEASUREMENT

UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT

UNIT

KGM

PACKAGING VOLUME

4302208

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8426436040090

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

4302208

UNITS CONTAINED PACKAGING

10

PACKAGING GROSS WEIGHT

0.46

UNITARY PACKAGING VOLUME

UNIT

MMQ

PACKAGING HEIGHT

116

PACKAGING NET WEIGHT

0.46

UNITARY PACKAGING GROSS

WEIGHT

0.046

PACKAGING WIDTH

122

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

304