

PD-25x3 Hallway HF+LUX BT Mesh surface KNX white IP20

REF. 89215736-230



BASIC INFORMATION

DESCRIPTION

Presence and ambient light detector for surface mounting HF. The recommended installation height is 2.8 m, with a maximum height of 4 m. It has a detection angle of 360 ° and an opening angle of 140 °. The tangential detection range is 25 x 3 m and the radial detection range is 25 x 3 m.

The luminosity regulation range is 10 - 1000 lux and the timing range is 10 s - 1092 min. The detector configuration is done via Bluetooth application and KNX.

It features a TEACH operating mode. Possibility of interconnection between sensors via KNX. The control protocol is KNX. The typical consumption is 30 mA.

The power supply voltage is KNX (21 - 30 VDC). The operating temperature of the detector is: -20 - 50 °C. White finish, IP 20 protection rating, and dimensions: 123 x 123 x 62 mm.

5-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

ETIM CLASS

EC001582

TECHNICAL INFORMATION

IP RATING

IP20

RAL

9003

POWER SUPPLY (V~)

Bus KNX (21 Vcc...32 Vcc)

CONTROL

KNX

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

2

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053342732

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.38

PRODUCT NET WEIGHT

0.265

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053342732

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

161

PACKAGING WIDTH

101

PACKAGING LENGTH

143

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

2325323

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.38

PACKAGING NET WEIGHT

0.265

PACKAGING WEIGHT UNIT

KGM