# Customisable kit with cover and fin, 2xUSB charger, 3 schuko socket outlets and 2 empty elements white S400 Indesk

REF. **45623000-130**



## BASIC INFORMATION

### DESCRIPTION

Provide maximum security in electrical systems is the raison d '®tre of Simon. In its range 400 highlights the kit is part of the table customizable with cover and fin, 2xUSB charger, 3 sockets of plugs SCHUKOS and 2 empty elements in white colour, with a current of 16 A and a voltage of 250 V ~, it is suitable to be flush mounted in furniture and compatible with all the functions of the series Simon 400 Indesk. Its measures are 340 x 185 x 85 mm One of its most outstanding qualities are: Insulation resistance > 5 M? at 500 V, connector figure Wieland ® gst18i with 3 poles male in-line with patch cord of 22 cm and dielectric strength with no holes or contours with 2000 V at 50H during a minute. It has been made with enclosure painted steel, profile in anodised aluminium, covers and fastenings in self-extinguishing thermoplastic and halogen-free; guarantees no flame propagation in case of fire and low toxicity in the event of smoke generation.

### FINISH

White

### MATERIAL

Metal

### COMPATIBILITY

Functions of the Simon 400 range, combinable with the Simon Electric Cabling range.

### PACKAGING CONTENTS

Pre-wired profile, enclosure, fastening claws and installation manual.

### ETIM CLASS

EC002759

### REMARKS

To complete the product installation combine it with the Simon 400 functions (refs. 400XXXXX-03X).

# TECHNICAL INFORMATION

### AVAILABLE MARKET
CE

### PROTECTION AGAINST DIRECT ACCESS OF CONTACTS
No

### PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS
Yes, thanks to the included protective cover and cable outlet with metal fin

### DIELECTRIC STRENGTH
No holes or contours, with 2000V at 50 Hz for 1 minute

### MAX TEMP DURING CONSTRUCTION WORK (°C)
+60°C

### NUMBER OF POSSIBLE ELEMENTS
2

### FORMAT
Schuko

### HEAT RESISTANCE (°C)
+70°C (according to standard IEC 60670)

### INSULATION RESISTANCE (V-MΩ)
>5 M? at 500 V

### CURRENT (A)
16 A

### IP RATING
IP30

### MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 at +60° C

### NOMINAL VOLTAGE (V~)
250 V~

### TYPE OF POWER SUPPLY CONNECTOR
Wieland® GST 18i male 3-pole overhead connector with 22 cm patch cord

### RAL
9016

### NUMBER OF REAR ENTRANCES
2

### RECESS DIMENSION (MM)
318 x 175 mm (± 2mm)

### NUMBER OF SOCKETS
3 sockets for standard current circuit

### NUMBER OF USB CHARGERS
1

### VERSION
6 elements

## INSTALLATION AND MAINTENANCE

### CABLING ACCESS
With metal fin

### CLAW RANGE OF OPERATION (MM)
Between 20 and 40 mm

### REMOVAL OF COMPONENTS

### NUMBER OF COVER OPENING POSITIONS
1

### EXTINGUISHING (°C)
+70 °C (according to standard IEC 60670)

### TYPE OF FASTENING
By lateral tightening of claws provided with the enclosure. Optional possibility to fasten the enclosure with screws through the provided holes in the sides of the enclosure chassis.

### REMOVAL OF THE FRAME
Only with tool

### INSTALLATION TYPE
Suitable for recessed mount in furniture.

### OPENING ORIENTATION
At 45

### REMOVAL OF THE PLATE
Only with tool

### SECURING POSSIBILITIES
Using supplied claws or screws in the available holes

### MOUNTING WITHOUT ACCESSORIES
Supplied with all necessary materials for installation.

## REGULATIONS

### REGULATIONS
Directiva 2014/35/UE LVD;Directiva 2014/30/UE EMC;Directiva 2011/65/UE RoHS;EN 50173-1:2011;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;EN 60950-1:2006;EN 60950-1:2006 A11:2009;EN 60950-1:2006 A1:2010;EN 60950-1:2006 A12:2011;EN 60950-1:2006 A2:2011*3;ETSI-EN 301489-34 V1.4.1;IEC 60884-1 Ed 3.2;

## LOGISTICS INFORMATION

UNITARY EAN CODE
8421053196939

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
2.35

PRODUCT NET WEIGHT
2.35

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053196939

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
365

PACKAGING WIDTH
195

PACKAGING LENGTH
90

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
6405750

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0

PACKAGING NET WEIGHT
2.35

PACKAGING WEIGHT UNIT
KGM