

## Switch for card 6 (2)A 250V~ with fast connection graphite Simon 24 Harmonie

REF. 2410526-038



### BASIC INFORMATION

#### FINISH

Graphite

#### PACKAGING CONTENTS

Mechanism

#### COMPATIBILITY

Simon 24 Harmonie frames

#### ETIM CLASS

EC001590

#### REMARKS

Recommended installation by linking the item to a relay. Otherwise, the switch's maximum current is 6A (inductive 2A).

## TECHNICAL INFORMATION

### AVAILABLE MARKET

CE, except for Spain, UK, Poland, Portugal, Andorra and Russia

### CABLE SECTION ADMITTED (MM)

From 0,5 mm

### CONSUMPTION INDICATOR (MA)

1 mA

### NUMBER OF POSSIBLE ELEMENTS

1 element

### IK CLASSIFICATION

01

### CURRENT (A)

6(2 ind.) A

### IP RATING

IP20

### TYPE OF MECHANISM

Key | Card

### OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

### STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

### VERSION

Single

### VOLTAGE (V~)

250 V~

## INSTALLATION AND MAINTENANCE

### INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal

### INSTALLATION TYPE

Flush-mounted or surface-mounted

### TYPE OF TERMINAL CONNECTION - FUNCTION 1

Faston

## LOGISTICS INFORMATION

### UNITARY EAN CODE

8421053198087

### UNITARY PACKAGING HEIGHT

0

### UNITARY PACKAGING WIDTH

0

### UNITARY PACKAGING LENGTH

0

### UNITARY PACKAGING MEASUREMENT UNIT

MMT

### UNITARY PACKAGING VOLUME

0

### UNITARY PACKAGING VOLUME UNIT

MMQ

### UNITARY PACKAGING GROSS WEIGHT

0.13

### PRODUCT NET WEIGHT

0.13

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING EAN

8421053348611

### UNITS CONTAINED PACKAGING

1

### PACKAGING HEIGHT

77

### PACKAGING WIDTH

39.5

### PACKAGING LENGTH

77

### PACKAGING MEASUREMENT UNIT

MMT

### PACKAGING VOLUME

234195.5

### PACKAGING VOLUME UNIT

MMQ

### PACKAGING GROSS WEIGHT

0

### PACKAGING NET WEIGHT

0.13

### PACKAGING WEIGHT UNIT

KGM