

Luminaire wall-mounted 707.31 2L NW Diffused White

REF. 70731130-884



BASIC INFORMATION

DESCRIPTION

Model luminaire wall-mounted for Lighting in indoor space, it is a spotlight range of the 707 Designed for lighting in working environments. It is a model of Luminaire with a type of lighting colour NW, with a diagram and values DIFFUSED optics character. Lighting category A with an electrical control of the Type ON-OFF, with a power of up to 12 W Luminaire designed for spotlight Installation and assembly in the wall, with design in colour, tone and finishes in White and measures 120x75x 60 mm

APPLICATION

Ambient lighting

PACKAGING CONTENTS

1 unit

ETIM CLASS

EC002892

TECHNICAL INFORMATION

FREQUENCY

50 Hz

DRIVER INCLUDED

Yes

LUMENS (LM)

750 lm

IP RATING

IP20

ELECTRICAL CLASS

Type 2

LUMENS/W

750 lm/12W

OPERATING TEMPERATURE RANGE (°C)

35 °C maximum

INTEGRATED POWER SUPPLY

Yes

OPTICS

Diffused

POWER SUPPLY (V~)

230 V~

L70 (°C)

30,000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

COLOR TEMPERATURE (K)

4000 K

LIGHT BEAM APERTURE ANGLE (°)

70-70°

POWER (W)

12 W

CONTROL

On/Off

COLOR TYPE

NW

SERVICE LIFE

30.000 h

CRI

80

LIGHTING EFFICIENCY (LM/W)

63 lm/W

CHROMATICS CRI ICONS

CRI
80

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

Wall

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Screw

REGULATIONS

WARRANTY

3 years 30,000 h

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053109984

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0.521

PRODUCT NET WEIGHT

0.521

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053109984

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

100

PACKAGING WIDTH

150

PACKAGING LENGTH

90

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

1.35

PACKAGING VOLUME UNIT

DMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

0.521

PACKAGING WEIGHT UNIT

KGM