Projector 889 300W 5500K

REF. **88936038-885**



BASIC INFORMATION

DESCRIPTION

Outdoor LED projector for showcase and facade lighting, robust, adjustable, and designed for high performance in commercial applications. Available in different power ratings, the outdoor projector 889 allows for selecting the appropriate model based on the mounting height, the surface to be illuminated, and the desired impact level. Installation type: Surface. Optics: 110. Color temperature: 5500K. Power: 300W. Lumens: 27000lm. Efficiency: 90lm/w. Protection rating IP: IP65. Power supply: 220-240 V. 50/60 Hz. Dimensions: 498 mm x 412 mm x 48 mm.

APPLICATION

Wall lighting,Industrial lighting,Commercial areas

TECHNICAL INFORMATION

FREQUENCY
50 - 60 Hz

IK CLASSIFICATION
05

IP RATING
IP65

OPERATING TEMPERATURE RANGE (°C)
-25...+50

POWER SUPPLY (V~)
220/240 V~

CONTROL
On/Off

LIGHTING EFFICIENCY (LM/W)
90 lm/W

LUMENS (LM)
27000 lm

OPTICS
Symmetric

POWER (W)
300 W

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE
Surface / Wall

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053440476

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
4.432

PRODUCT NET WEIGHT
4.28

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053440476

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
435

PACKAGING WIDTH
130

PACKAGING LENGTH
525

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
29688750

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
8.864

PACKAGING NET WEIGHT
4.28

PACKAGING WEIGHT UNIT
KGM