

# Kit Flash 90 consisting of swiss modular power socket, USB Type C Dock including 1x HDMI + LAN + 3x USB Type A, USB charger Type C 20W and grommet (cable outlet) white Simon K45

REF. KR3381301/9



## BASIC INFORMATION

### DESCRIPTION

Kit Flash 90 based on a modular swiss power socket-outlet for installation in furniture with an optional protective lid to allow it to be closed and hide the connections when not in use. Includes a USB Type-C dock with 1 HDMI output for display, 1 Gigabit Ethernet port, and 3 USB Type-A connectors for keyboard, mouse, and any other connection device based on the USB Type-A connector. The kit includes a 20W USB Type-C charger and a cable outlet in a white finish. Supplied with a 20cm long patch cable terminated in a 3-pole Wieland® Gst18i male aerial quick connector with a safety anchor to facilitate safe connection and disconnection from the mains without interrupting the power supply. The kit is supplied assembled with the internal connections pre-made. It is only necessary to make the die in the furniture where the product will be fixed and once done, connect it to the mains for it to be functional. It requires ordering the dock power supply separately (ref. CR6100121150201/14)

### FINISH

White

### MATERIAL

Plastic

### ETIM CLASS

EC002759

## TECHNICAL INFORMATION

### AVAILABLE MARKET

CE

### CURRENT (A)

10 A

### SNAP-FIT RJ45 PLATES

Directly to the Dock

### PROTECTION AGAINST DIRECT ACCESS OF CONTACTS

Yes

### IP RATING

IP20

### SNAP-FIT TYPE

Embedded in the dock

### PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS

Protective lid available (as an option) to protect the connections against entry of dust and small objects

### MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### USB CHARACTERISTICS

Charging

### RJ45 CONNECTORS

Yes

### NOMINAL VOLTAGE (V~)

250 V~

### USB CURRENT (A)

2,2 A

### CONNECTOR TYPE

Swiss

### RAL

9003

### POWER DELIVERY USB

Yes

### NUMBER OF CONTACTS

3

### RECESS DIMENSION (MM)

ø80 mm

### QUICK CHARGE USB

Yes

### FORMAT

Swiss

### RJ45 ADAPTOR MODULE

Yes

### USB VOLTAGE (V~)

9 V~

### VOLTAGE (V~)

250 V~

## INSTALLATION AND MAINTENANCE

### REMOVAL OF COMPONENTS

No tools needed

### REMOVAL OF COVER

Only with tool

### EXTINGUISHING (°C)

+650 °C (according to standard IEC 60670)

## REGULATIONS

### REGULATIONS

Dir. 2014/35/UE LVD\*1 | Dir. 2014/30/UE EMC\*3 | Dir. 2011/65/UE RoHS + post. mod.\*1 | Dir. 2009/125/EC ErP (Reg. UE 2019/1782) \*1 \*13 \*12 | S.I. 2016 No. 1101 - The Electrical Equipment (Safety) Regulations 2016\*2 | S.I. 2012 No. 3032 - The Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2012\*2 | IEC 60884-1 Ed.3.2\*1 | BS 1363-2:2016+A1:2018\*2 | UNE 20315-1-1:2017\*5 | BS 1363-4:2016+A1:2018\*2 | UNE 20315-1-2:2017\*5 | DS 60884-2-D1:2023\*4 | CEI 23-50 V4\*7 | SANS 164-1:2021\*6 | SN 441011-2-1:2019\*9 | SI 32 Fig. 204 B\*8 | AS/NZS 3112:2017\*11 | EN 50173-1:2018\*10 | EN 50563:2011 + A1:2013\*13 \*12 | EN 55032:2015 + A11:2020 + A1:2020\*12\*14 \*16 | EN 62368-1: 2014 + A11:2017\*13 \*12 | EN 55035:2017 + A11:2020\*12\*14 \*16 | ETSI-EN 301489-34 V2.1.1\*13 | EN IEC 61000-3-2:2019 + A1:2021 + A2:2024\*12 \*16 | EN IEC 60670-1:2021+ A11:2021\*15 | EN 61000-3-3:2013 +A1:2019 + A2:2021 \*12 \*16 | EN IEC 63000:2018

## LOGISTICS INFORMATION

### UNITARY EAN CODE

8421053398487

### UNITARY PACKAGING HEIGHT

0

### UNITARY PACKAGING WIDTH

0

### UNITARY PACKAGING LENGTH

0

### UNITARY PACKAGING MEASUREMENT UNIT

MMT

### UNITARY PACKAGING VOLUME

0

### UNITARY PACKAGING VOLUME UNIT

MMQ

### UNITARY PACKAGING GROSS WEIGHT

0.793

### PRODUCT NET WEIGHT

0.633

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING EAN

8421053398487

### UNITS CONTAINED PACKAGING

1

### PACKAGING HEIGHT

120

### PACKAGING WIDTH

130

### PACKAGING LENGTH

252

### PACKAGING MEASUREMENT UNIT

MMT

### PACKAGING VOLUME

3931200

### PACKAGING VOLUME UNIT

MMQ

### PACKAGING GROSS WEIGHT

0.793

### PACKAGING NET WEIGHT

0.633

### PACKAGING WEIGHT UNIT

KGM