

Industrial luminaire 816.43 5000K INT

REF. 81643038-385



BASIC INFORMATION

APPLICATION

Accent lighting, General lighting

ETIM CLASS

EC001716

TECHNICAL INFORMATION

IK CLASSIFICATION

08

L70 (°C)

50.000 h at 25°C

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

IP RATING

IP65

LIGHTING EFFICIENCY (LM/W)

137 lm/W

POWER (W)

200 W

COLOR TEMPERATURE (K)

5000 K

LUMENS (LM)

27400 lm

SERVICE LIFE

50.000 h

CONTROL

On/Off

LUMENS/W

27400 lm / 200W

CRI

80

OPTICS

Intensive

CHROMATICS CRI ICONS

CRI
80

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

Discontinued

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053229279

UNITARY PACKAGING HEIGHT

190

UNITARY PACKAGING WIDTH

420

UNITARY PACKAGING LENGTH

420

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

33516000

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

5.9

PRODUCT NET WEIGHT

4.8

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053229279

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

190

PACKAGING WIDTH

420

PACKAGING LENGTH

420

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

33516000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

5.9

PACKAGING NET WEIGHT

4.8

PACKAGING WEIGHT UNIT

KGM