

Switch for blinds 10A 250V~ with 3 positions: up, down and stop white Simon 27 Play

REF. 27333-64



BASIC INFORMATION

DESCRIPTION

The type is mechanical latching, it belongs to the Simon 27 Play range and in the categories of control of blinds, has a current of 10 A and a voltage of 250 V~ medium element and acomoda 3 positions: Raise, lower and stop, it also has a mechanism equipped with position control unit, i.e., allows you to stop the raising and lowering of the shutter. It has tilting operation and is suitable for 1 module, for its installation it will suffice to apply pressure or place on the surface. The wire section admitted is from 1.5 to 2.5 mm and has 11 mm of bare wire. The material is socket metal components with halogen-free thermoplastic insulation and thermoset trim, being able to oscillate between 5 and 40°, and can support up to a maximum of between -25 and 50° C, this article complies perfectly with the regulation EN 60669-1: 1999 + A1: 2002 + A2: 2008 + EN 50581: 2082. The dimensions are 22.5x45 mm, although it is available in other sizes and colors. To keep the piece clean, use a soft and dry cloth, under no circumstances be poured abrasive cloths or cleaners with high chlorine content.

FINISH

White

COMPATIBILITY

Simon 27 Play, Simon 27 Neos, Simon 27 Scudo, Simon 27, Simon 27 Centralisations and Simon 44 Aqua frames

PACKAGING CONTENTS

Mechanism with rocker

ETIM CLASS

EC000044

REMARKS

Mechanism with centre position to stop the up/down movement of the blinds.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CURRENT (A)

10 A

TYPE OF MECHANISM

Pivoting

CABLE SECTION ADMITTED (MM)

From 1,5 to 2,5 mm

IP RATING

IP20

OPERATING TEMPERATURE

RANGE (°C)

5 - 40 °C

NUMBER OF POSSIBLE ELEMENTS

Half element

LATCH TYPE

Mechanical

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

INDICATOR FUNCTION

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

VERSION

Single

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

11

CLAW

Simon 27

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, American, Small
spaces and Centralisations

INSTALLATION TYPE

Suitable for surface and flush
mounting

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Fast

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2011/65/UE RoHS + post. mod. | EN 60669-1:2018 | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053252000

UNITARY PACKAGING HEIGHT

22.8

UNITARY PACKAGING WIDTH

39.2

UNITARY PACKAGING LENGTH

46

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0.041

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.03

PRODUCT NET WEIGHT

0.026

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053080825

UNITS CONTAINED PACKAGING

5

PACKAGING HEIGHT

55.5

PACKAGING WIDTH

54

PACKAGING LENGTH

131.8

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

0.395

PACKAGING VOLUME UNIT

DMQ

PACKAGING GROSS WEIGHT

0.15

PACKAGING NET WEIGHT

0.13

PACKAGING WEIGHT UNIT

KGM